



Main

Product	Single Throw Safety Switch
Current Rating	30 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 1
Disconnect Type	Non-fusible disconnect switch
Factory Installed Neutral	None
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	General duty
Voltage Rating	240 V AC
Wire Size	AWG 14...AWG 6 copper AWG 12...AWG 6 aluminium

Complementary

Short-circuit withstand	200 kA
Maximum Horse Power Rating	3 Hp 240 V AC 60 Hz 1 phase NEC 430.52 7.5 hp 240 V AC 60 Hz 3 phase NEC 430.52
Maximum Width	7.25 in (184.15 mm)
Maximum Height	9.25 in (234.95 mm)
Maximum Depth	3.63 in (92.20 mm)
Tightening torque	30 lbf.in (3.39 N.m) 0.00...0.02 in ² (2.08...13.3 mm ²) AWG 14...AWG 6)

Ordering and shipping details

Category	00006 - D & DU SW, NEMA1, 30-200A
Discount Schedule	DE1A
GTIN	00785901491606
Nbr. of units in pkg.	1
Package weight(Lbs)	4.25 lb(US) (1.93 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.20 in (13.208 cm)
Package 1 width	7.00 in (17.78 cm)
Package 1 Length	9.20 in (23.368 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	5
Package 2 Weight	22.75 lb(US) (10.319 kg)
Package 2 Height	10.10 in (25.654 cm)
Package 2 width	8.80 in (22.352 cm)
Package 2 Length	19.10 in (48.514 cm)
Unit Type of Package 3	PAL
Number of Units in Package 3	200
Package 3 Weight	924.00 lb(US) (419.119 kg)

Package 3 Height	44.00 in (111.76 cm)
Package 3 width	40.00 in (101.6 cm)
Package 3 Length	48.00 in (121.92 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------