# Product data sheet Characteristics

# HOM4080L225PQGC

Load center, Homeline, 1 phase, 40 spaces, 80 circuits, 225A convertible main lugs, PoN, NEMA1, Qwik-grip, grnd bar



#### Main

Widin	
Product Type	Load Center
Marketing Trade Name	Homeline
Load Center Type	Main lugs
Rated Current	225 A
Number of Spaces	40
Number of Circuits	80
Enclosure Rating	NEMA 1 indoor
Cover Type	Combination flush/surface cover
Electrical Connection	Lugs
Included Options	Grounding bar 1) Qwik grip assembly kit 1)

#### Complementary

Short Circuit Current Rating	10 kA	
Number of Tandem Breakers	40	
Number of Phases	1 phase	
Rated Operational Voltage	120/240 V AC	
Wire Size	AWG 4250 kcmil aluminium/copper	
Wiring Configuration	3-wire	
Enclosure Material	Welded galvannealed steel	
Surface Finish	Baked enamel Gray	
Box Number	12Q	
Height	39.37 in (1000 mm)	
Width	14.25 in (362 mm)	
Depth	3.74 in (95 mm)	

#### Environment

Ambiant Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)	
Product Certifications	UL	

#### Ordering and shipping details

Category	00045 - HOM LC&CVR,12-42 CKT,NEMA1
Discount Schedule	DE3C
GTIN	00785901619369
Nbr. of units in pkg.	1
Package weight(Lbs)	32.39 lb(US) (14.69 kg)
Returnability	Yes
Country of origin	US

## Packing Units

PCE	
PAL	
18	
682.00 lb(US) (309.35 kg)	
37.80 in (96.012 cm)	
40.00 in (101.6 cm)	
48.00 in (121.92 cm)	
	PAL  18  682.00 lb(US) (309.35 kg)  37.80 in (96.012 cm)  40.00 in (101.6 cm)

## Offer Sustainability

REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	