

**Product Number:** 64270

**Order Abbreviation:** MCP39/PAR30LN/U/830/FL/ECO PB

**General Description:** 39W high CRI, powerball arc tube, reduced color shift, high performance, ECO open fixture rated PAR30 lamp clear, flood, universal

#### Product Information

Abbrev. With Packaging Info.	MCP39PAR30LNU830FLECO PB 6/CS 1/SKU
ANSI Code	C130/O
Approx. Lumens (initial - horizontal)	2550
Average Rated Life - Horizontal (hr)	15000
Average Rated Life - (hr)	15000
Average Rated Life - Vertical (hr)	15000
Base	E26 Medium
Beam Angle (deg)	30
Bulb	PAR30LN
Color Rendering Index (CRI)	85
Color Temperature/CCT (K)	3000
Diameter (in)	3.740
Diameter (mm)	95.00
Family Brand Name	Metalarc® Powerball
Lamp Finish	Clear
Nominal Voltage (V)	90.00
Nominal Wattage (W)	39.00



#### Footnotes

- Use with 4000V pulse rated sockets only.
- Passes Federal TCLP test based on NEMA LL Series Standards. TCLP data available upon request. Disposal regulations may vary depending on location. Please check your local and state/provincial regulations.
- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaires. See lamp warning.
- The circuit must include overcurrent protection (I.e. Thermally switched ballast).
- Lamp requires a nominal Open Circuit Voltage of 230V or higher. Without an ignitor in the circuit minimum OCV is 209Vrms.
- UV-Stop quartz
- Approved electronic ballast is required, view approved ballast list in Product documents, graphs and images.