



## Main

Range of product	Motor Logic
Product destination	Starter
Thermal overload type	Solid state

## Complementary

NEMA size	2
Phase	3 phase
Mounting support	Mounting plate
[Ue] rated operational voltage	600 V AC
Height	3.51 in (89.2 mm)
Width	4.28 in (108.7 mm)
Maximum Depth	3.51 in (89.2 mm)

## Ordering and shipping details

Category	21662 - 9065 SOLID STATE OVERLOAD RELAYS
Discount Schedule	CP1
GTIN	00785901750017
Nbr. of units in pkg.	1
Package weight(Lbs)	1.24 lb(US) (0.56 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Package 1 Height	5.20 in (13.208 cm)
Package 1 width	5.50 in (13.970 cm)
Package 1 Length	5.80 in (14.732 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
RECh Regulation	 <a href="#">RECh Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes

RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes

### Contractual warranty

Warranty	18 months
----------	-----------