



Product Number: 64469

Order Abbreviation: M1000/U/BT37

General Description: 1000W METALARC compact quartz metal halide lamp, reduced outer jacket, E39 base, BT37 bulb, enclosed fixture rated, universal burn, clear, 3800K

Product Information

| | |
|---------------------------------------|-----------------------|
| Abbrev. With Packaging Info. | M1000UBT37 6/CS 1/SKU |
| ANSI Code | M47/E |
| ANSI Code 2 | M47/E |
| Approx. Lumens (initial - horizontal) | 100500 |
| Approx. Lumens (initial - vertical) | 110000 |
| Approx. Lumens (mean - horizontal) | 86000 |
| Approx. Lumens (mean - vertical) | 93500 |
| Arc Length (in) | 3.58 |
| Arc Length (mm) | 91 |
| Average Rated Life - Horizontal (hr) | 9000 |
| Average Rated Life - (hr) | 9000 |
| Average Rated Life - Vertical (hr) | 15000 |
| Base | E39 Mogul |
| Bulb | BT37 |
| Color Rendering Index (CRI) | 65 |
| Color Temperature/CCT (K) | 3800 |
| Diameter (in) | 4.606 |
| Diameter (mm) | 117.00 |
| Family Brand Name | Compact Metalarc® |
| Fixture Requirement | E |
| Hot Restrike Time (min) | 7-12 |
| Lamp Finish | Clear |
| Light Center Length - LCL (in) | 7 |
| Light Center Length - LCL (mm) | 178 |
| Maximum Base Temperature - Fahrenheit | 482 |
| Maximum Base Temperature - Celsius | 250 |
| Maximum Bulb Temperature - Fahrenheit | 806 |
| Maximum Bulb Temperature - Celsius | 430 |
| Maximum Overall Length - MOL (in) | 11.5 |
| Maximum Overall Length - MOL (mm) | 292 |
| Nominal Voltage (V) | 263.00 |
| Nominal Wattage (W) | 1000.00 |
| Operating Position | Universal |
| Warm-up Time (min) | 2-4 |

Footnotes

- E = Lamps classified as E-type are to be used ONLY in suitably enclosed luminaries. See lamp warning.