



Note:
 - Drawings Not To Scale
 - Drawings Subject to Change Without Notice
 - Dimensions are inches next to [Millimeters]

Part No.:

9080LBA363106



Schneider Electric United States
 North American Division
 Boston One Campus
 800 Federal Street
 Andover, MA 01810, USA
 Phone: +1 8773425173
 Email: CCC@us.schneider-electric.com

Technical Information:

| | |
|----------------------|-------------------------|
| For Use With: | Copper or Aluminum Wire |
| Terminal Type: | Lugs |
| Cover: | 9080LB33 |
| Service Class: | C |
| UL File: | E60616 XCFR2 |
| CSA File: | 70361 6228-01 |
| RoHS: | Yes |
| CE Marked: | Yes |
| Flammability Rating: | UL94V-0 |
| 35mm Track Adapter: | N/A |

| | |
|--|------------------------|
| Description: | |
| Ampere Rating: | 335A/270A (Cu/Al) |
| Max. Voltage Rating: | 600V AC/DC |
| Number of Poles: | 3 |
| Wire Range - Main: | (1)#6 to 400 AWG/kcmil |
| Wire Range - Branch: | (6)#14 to #2 AWG |
| Short Circuit Current Ratings with Circuit Breakers: | Up to 65 kA |
| Short Circuit Current Ratings with Fuses: | Up to 200kA |

Specification: