



Main

Product	Single Throw Safety Switch
Current Rating	200 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 3R
Disconnect Type	Non-fusible disconnect switch
Factory Installed Neutral	None
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	General duty
Voltage Rating	240 V AC
Wire Size	AWG 6...250 kcmil aluminium/copper

Complementary

Short-circuit withstand	200 kA
Maximum Horse Power Rating	15 Hp 240 V AC 60 Hz 1 phase NEC 430.52 60 hp 240 V AC 60 Hz 3 phase NEC 430.52
Maximum Width	19 in (482.60 mm)
Maximum Height	29 in (736.60 mm)
Maximum Depth	8.25 in (209.55 mm)
Tightening torque	275 lbf.in (31.07 N.m) AWG 6...250 kcmil

Ordering and shipping details

Category	00106 - D & DU SW,NEMA3R, 30-200A
Discount Schedule	DE1A
GTIN	00785901491880
Nbr. of units in pkg.	1
Package weight(Lbs)	44.85 lb(US) (20.34 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	8.70 in (22.098 cm)
Package 1 width	19.40 in (49.276 cm)
Package 1 Length	30.80 in (78.232 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	15
Package 2 Weight	652.00 lb(US) (295.742 kg)
Package 2 Height	46.00 in (116.84 cm)
Package 2 width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------