


# Product data sheet

## Characteristics

# 9080MH239

Terminal block, Linergy, mounting track, 35 mm  
DIN rail, no mounting holes, 39.37 inches long



### Main

Range	9080G
Product	DIN rail
Quantity per set	Set of 10

### Complementary

Material	Galvanised steel
Height	0.3 in (7.62 mm)
Width	1.38 in (35.05 mm)
Length	39.37 in (1000.00 mm)

### Ordering and shipping details

Category	21716 - 9080 M - DIN RAIL & END CLAMP
Discount Schedule	CP5
GTIN	00785901035688
Nbr. of units in pkg.	10
Package weight(Lbs)	0.74 lb(US) (0.34 kg)
Returnability	Yes
Country of origin	US

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.51 in (1.3 cm)
Package 1 width	1.30 in (3.3 cm)
Package 1 Length	39.41 in (100.1 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Weight	8.58 lb(US) (3.892 kg)
Package 2 Height	2.80 in (7.112 cm)
Package 2 width	2.80 in (7.112 cm)
Package 2 Length	51.40 in (130.556 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------