

Product data sheet

Characteristics

D211N

Safety switch, general duty, fusible, 30A, 2 poles, 3 hp, 120 VAC, NEMA 1, neutral factory installed



Main

Product	Single Throw Safety Switch
Current Rating	30 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 1
Disconnect Type	Fusible disconnect switch
Factory Installed Neutral	Neutral/earth strip 2 x 16 mm ² 5 x 6 mm ²
Short Circuit Current Rating	10 kA plug
Mounting Type	Surface
Number of Poles	2
Electrical Connection	Lugs
Duty Rating	General duty
Voltage Rating	120 V AC
Wire Size	AWG 14...AWG 6 copper AWG 12...AWG 6 aluminium

Complementary

Maximum Horse Power Rating	0.5 Hp 120 V AC 60 Hz 1 phase NEC 240.6 2 Hp 120 V AC 60 Hz 1 phase NEC 430.52 1.5 Hp 240 V AC 60 Hz 1 phase NEC 240.6 3 hp 240 V AC 60 Hz 1 phase NEC 430.52
Width	7.25 in (184.15 mm)
Height	9.25 in (234.95 mm)
Maximum Depth	3.63 in (92.20 mm)
Tightening torque	30 lbf.in (3.39 N.m) 0.00...0.02 in ² (2.08...13.3 mm ²) AWG 14...AWG 6)

Ordering and shipping details

Category	00006 - D & DU SW, NEMA1, 30-200A
Discount Schedule	DE1A
GTIN	00785901460329
Nbr. of units in pkg.	1
Package weight(Lbs)	4.17 lb(US) (1.89 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.50 in (13.97 cm)
Package 1 width	7.00 in (17.78 cm)
Package 1 Length	9.50 in (24.13 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	5
Package 2 Weight	22.25 lb(US) (10.092 kg)
Package 2 Height	9.80 in (24.892 cm)
Package 2 width	8.40 in (21.336 cm)
Package 2 Length	19.00 in (48.26 cm)

Unit Type of Package 3	PAL
Number of Units in Package 3	150
Package 3 Weight	668.00 lb(US) (302.999 kg)
Package 3 Height	40.00 in (101.6 cm)
Package 3 width	40.00 in (101.6 cm)
Package 3 Length	48.00 in (121.92 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------