HOM24L70RB

Load center, Homeline, 1 phase, 2 spaces, 4 circuits, 70A fixed main lugs, NEMA3R





Main

mani	
Product Type	Load Center
Marketing Trade Name	Homeline
Load Center Type	Main lugs
Rated Current	70 A
Number of Spaces	2
Number of Circuits	4
Enclosure Rating	NEMA 3R outdoor
Cover Type	Surface cover
Electrical Connection	Lugs

Complementary

10 kA	
2	
1 phase	
120/240 V AC	
AWG 12AWG 3 aluminium AWG 14AWG 4 copper	
3-wire	
Gray baked enamel	
Tin plated aluminium busbar	
Welded galvannealed steel	
Baked enamel Gray	
1R	
9.37 in (238 mm)	
4.88 in (124 mm)	
4.02 in (102 mm)	
	2 1 phase 120/240 V AC AWG 12AWG 3 aluminium AWG 14AWG 4 copper 3-wire Gray baked enamel Tin plated aluminium busbar Welded galvannealed steel Baked enamel Gray 1R 9.37 in (238 mm) 4.88 in (124 mm)

Environment

Ambiant Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL E-6294

Ordering and shipping details

DE3C
00785901061175
1
4.95 lb(US) (2.25 kg)
Yes
MX

Packing Units

	202	
Unit Type of Package 1	PCE	
Package 1 Height	4.80 in (12.192 cm)	
Package 1 width	5.70 in (14.478 cm)	
Package 1 Length	11.00 in (27.94 cm)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	71	
Package 2 Weight	356.92 lb(US) (161.895 kg)	
Package 2 Height	40.00 in (101.6 cm)	
Package 2 width	40.00 in (101.6 cm)	
Package 2 Length	48.00 in (121.92 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	Lifetime