


TYPE SPA

Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Chamfered wire entry
- Rounded bottoms
- Large screw diameters
- Wire stop in center
- Suitable for use in circuits rated 35KV or less, proper high voltage spacing and insulation techniques must be used
- Rated to 90° C

Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of installation
- Facilitates taping
- Ensures all wire strands are held securely
- Prevents dissimilar metals coming into contact
- Application versatility



C

Catalog Number	Wire Range	Dimensions			Number of Screws	Screw Diameter	Hex Size
		L	W	H			
SPA-2	2-14	1-3/16	29/64	9/16	2	3/8	Slot
SPA-0	1/0-14	1-29/32	5/8	11/16	2	7/16	3/16
SPA-250	250kcmil-6	2-5/16	7/8	1	2	5/8	5/16
SPA-350	350kcmil-10	2-15/32	1	1-1/4	2	11/16	5/16
SPA-500	500kcmil-4	3-7/8	1-1/8	1-5/8	2	13/16	3/8
SPA-750	750kcmil-250kcmil	5-7/16	1-3/8	1-3/4	4	15/16	1/2
SPA-1000	1000kcmil-500kcmil	8-11/16	1-3/4	1-3/4	6	1-1/8	9/16

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)
DE-OX Inhibitor is recommended for all aluminum terminations.
Tested to UL 486A/B, UL File E6207