

CAT6 - FTP - Foil Twisted Pairs

CAT6 - FTP - Foil Twisted Pairs
4 Pair - 23 AWG - 250 MHz
CMR

Category Conductor Description:

- Solid bare copper

Category Insulation Description:

- High-Density Polyethylene (HDPE)

Shield:

- Aluminum/Mylar tape with tinned copper drain wire

Category Jacket Description:

- Polyvinyl Chloride (PVC)

Standards:

- CMR FTP
- EIA/TIA 568B
- Non Plenum - CMR
- ISO/IEC11801
- ETL/UL Available

Color Code Chart	
# of Pairs	Color
1	Blue & White/Blue Stripe
2	Orange & White/Orange Stripe
3	Green & White/Green Stripe
4	Brown & White/Brown Stripe

Part Number Table

Part#	Gauge	Pairs	Outside Diameter Inches	Material Weight (Lbs./M')
J662304-01	23	4	0.284	44
J662304-DB	23	4	0.284	44

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances * -DB is rated for Direct Burial

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC