

WHITLAM



Thread Sealing Compound

T-U TYPE 555 is a yellow soft-set, odor free, all purpose, non-seizing, thread sealing compound that produces a leak proof seal on all types of metal and plastic threaded connections. **T-U TYPE 555** is completely homogenized and free of any valve destroying grit. Temperature Range Use: -50°F (-45°C) to 400°F (+204°C).

- Non-Separating
- Grit Free Paste
- Adheres to Oily Threads
- Easy Cleanup
- Safe for PVC & CPVC
- Nontoxic/Non Combustible

Suitable for use on systems carrying:

| | | | |
|--------------------|-----------------|--------------------|----------------|
| Acids, Dilute | Cutting Oils | Kerosene | Soap, Liquid |
| Air, Compressed | Diesel Fuel Oil | LP Gases | Steam Lines |
| Aliphatic Solvents | Freons (All) | Lacquer | Sugar, Liquid |
| Alkalis, Dilute | Gasoline | Mineral Oils | Vegetable Oils |
| Ammonia | Glycol | Natural Gas | Water |
| Brine | Heating Oils | Nitrogen Gas | |
| Butane | Helium, Gaseous | Petroleum Solvents | |
| Carbon Dioxide | Hydraulic Oils | Propane | |
| Castor Oils | Hydrogen | Refrigeration | |
| Chlorinated Water | Inert Gases | Gases | |
| Coal Tar Naphtha | Jet Fuel | | |

FOR USE ON THREADED:

ABS, PVC, CPVC, Delrin*, Zytel*, FlowGuard GOLD** CPVC, Blazemaster** CPVC, Fiberglass, Nylon, Polypropylene, Polybutylene, Polyethylene, Celcon***, Cynolac****, and all types of metal.

PRESSURE RANGE USE:

Gases:

Up to 3,000 PSI (211 kg/cm²)

Liquids:

Up to 6,000 PSI (422 kg/cm²)

U.S. FEDERAL SPECIFICATIONS

T-U TYPE 555 exceeds TT-S-1732

AVAILABLE SIZES

| | |
|--------|-------------------|
| Stock# | Size |
| TU4 | 1/4 pint (118 ml) |
| TU8 | 1/2 pint (237 ml) |
| TU16 | 1 pint (473 ml) |
| TU32 | 1 quart (.95 L) |
| TU1 | 1 gal. (3.785 L) |
| TU5 | 5 gal. (18.9 L) |
| TU55 | 55 gal. (208 L) |

*Dupont registered trademarks

** FlowGuard Gold and Blazemaster are

Lubrizol registered trademarks

***Celanese registered trademark

****General Electric Plastics registered trademark



Approved for Natural Gas, Propane, LP Gas and Butane.



NSF Standard 14
NSF Standard 61



"For a Positive Leak-proof Seal"

Distributed By:



J.C. Whitlam Manufacturing Co.
P.O. Box 380 • Wadsworth, OH 44282
U.S. & Canada

Phone: 800-321-8358

FAX: 800-537-0588

International

Phone: 330-334-2524

FAX: 330-334-3005

www.joinpipe.com

