

**1G66-641**

LINE VOLTAGE BIMETAL WALL THERMOSTATS

Electric Heat Thermostats used for Controlling Baseboards, Cable Heat, Glass Panels, etc.

FEATURES

- 1G66 types are a double-pole disconnect model with "OFF" position which mechanically breaks both sides of line.
- Classic white.

SPECIFICATIONS

Dimensions 4¹³/₁₆" H x 3⁵/₁₆" W x 1⁷/₁₆" D

Agency U.L. listed and C.S.A. certified

PARTS AND ACCESSORIES

See end of this section for additional parts and accessories

- F61-2685 – Wallplate (4³/₁₆" x 5¹/₁₆")
- Thermostat guards – see pages 26-27

	Model Number	Range	Differential	Switch Action	Resistive (Non-Inductive)
NEW!	1G65-641	40 to 80°F (4 to 26°C)	2.0°F	Open on Rise	22.0A, 120 VAC (2500W) 22.0A, 240 VAC (5000W) 18.0A, 277 VAC (5000W)
NEW!	1G66-641	40 to 80°F (4 to 26°C)	2.0°F	Open on Rise	22.0A, 240 VAC (5000W) 18.0A, 277 VAC (5000W)
NEW! 🍁	1G65-633	40 to 80°F (4 to 26°C)	1.0°F	Open on Rise	22.0A, 120 VAC (2500W) 22.0A, 240 VAC (5000W) 18.0A, 277 VAC (5000W)
NEW! 🍁	1G66-633	40 to 80°F (4 to 26°C)	1.0°F	Open on Rise	22.0A, 240 VAC (5000W) 18.0A, 277 VAC (5000W)

🍁 Indicates Canadian Model Number: call 1-905-201-4653 to order

www.white-roddgers.com