

## Instructions

Please refer to Owner's Manual for complete operating instructions.

- 4-cycle, single cylinder, air-cooled gasoline engine
- Excellent for high volume water transfer
- Unrestricted flow 40 gallons per minute
- 1" inlet/outlet diameter
- Includes two (2) 6' hoses for intake and discharge, garden hose adapter, and strainer



## Parts Included



Siphon King<sup>®</sup> Gas Powered Pump

Catalog #	ltem	Selling Unit
48350	Gas Powered Pump	1 per box



- A 6' Hose
- **B** Oil
- C Strainer
- D Garden Hose Adapter
- E Large O-Ring Seal (Garden Hose Adapter)
- **F** Hose Adapter #2
- G Wrench
- H Small O-Ring Seal (Hose)
- I Hose Adapter #1
- J Hose Clamps





## Siphon King® Gas Powered Pump

Siphon King® Gas Powered W	ater Pump - Technical Specifications		
General			
Product Name	Siphon King <sup>®</sup> Gas Powered Water Pump		
Model Number (SKU)	48350		
Length	11.5″		
Width	11.5″		
Height	13″		
Weight	18.9 lbs		
Packaging Dimension	16.5" x 12.6" x 14.6"		
Engine			
Engine Type	4-Cycle, Single Cylinder		
Displacement	40 cc		
Cooling System	Air Cooled		
Ignition System	Transistor Magneto		
Starting System	Recoil Starter		
Operating Mode	Continuous Operation		
Engine Oil	SAE 10W-30 or 10W-40 API SM		
Engine Oil Capacity	2.7 oz		
Fuel	Unleaded; 86 or higher		
Fuel Tank Capacity	0.2 US gal		
Spark Plug Gap	0.024″		
Idle Speed	3,300 ± 100 r/min		
Pump			
Suction Port Diameter	1.0″		
Discharge Port Diameter	1.0″		
Max. Total Head	82 ft		
Max. Suction Head	25 ft		
Discharge Capacity	39.6 gal/min (max)		