TECHNICAL SPECIFICATIONS

S-36

MODEL NUMBER 141022

DIMENSIONS: 36" x 36" x 72" Gelcoat





国 Minimum Alcove Depth Opt Unit Rough-In Depth		or Drain	in Installat	Drain Drain Lut-Out Lib	Finished Unit Depth
Model	А	В	С	D	E
141022	36"	37 1/2"	36"	18"	18"

	вчМААХ

STANDARD FEATURES

- One-piece gelcoated fiberglass shower with optional roofcap
- Built-in corner shelves
- Center drain
- Textured floor
- Optional unique features: above-the-floor rough
- Reinforced walls

UNIQUE FEATURES

• Above-the-Floor Rough (AFR)

OPTIONS

- Gelcoated fiberglass cap
- Light for roofcap (factory-drilled hole)
- · All walls reinforced
- · Lifter for Pivolok Doors
- Wall reinforcement (one wall)

SYSTEMS

• None

DOOR SELECTION

Combine with AKER's complete shower door offering visit www.akerbymaax.com

CERTIFICATIONS

AKER products adhere to one or more of the following certifications:







Project :

Contractor :

AKER Representative : Tel :

Date :

TECHNICAL SPECIFICATIONS



S-36

MODEL NUMBER 141022

TECHNICAL DRAWINGS

With reinforcement





