TECHNICAL SPECIFICATIONS


TS-3660

MODEL NUMBER 141227

DIMENSIONS: 59 7/8" x 35 7/8" x 75 1/8" Gelcoat







NOTE: Left End Drain Installation Illustrated Note: Left End Drain Installation Illustrated											
Alcove Length / Unit Length											
Model	А	В	С	D	E						
141227	59 7/8"	37 3/8"	35 7/8"	18 5/8"	8 1/4"						

	1412	27	59 7/8"	37 3/8"	35 7/8"	18 5/8"	8 1/4"
Project :					1		
-							
Contractor:							
AKER Representative :					Tel:		
Date :							



STANDARD FEATURES

- One-piece gelcoated fiberglass tub-shower
- Built-in top corner shelves and integrated soap dish
- Right or left-hand drain
- Textured floor
- 14 1/2 inch deep sump
- Bottom bathing well: 44 inch L x 21 3/8 inch W
- Optional unique features: Above-the-Floor Rough and reinforced walls

UNIQUE FEATURES

• Above-the-Floor Rough (AFR)

OPTIONS

- In-line heater (factoryinstalled)
- Pump position opposite standard position
- All walls reinforced
- Wall reinforcement (one wall)

SYSTEMS

Homestead DOOR

SELECTION

Combine with AKER's complete shower door offering visit www.akerbymaax.com

CERTIFICATIONS

AKER products adhere to one or more of the following certifications:







TECHNICAL SPECIFICATIONS





TS-3660


MODEL NUMBER 141227


TECHNICAL DRAWINGS

STANDARD









REINFORCEMENT BACKING

Right wall reinforcement shown Left wall reinforcement symmetrical

