

## NRDD Recovery Unit



## Light • Fast • Compact

### Brushless DC Motor

- Light
- More efficient

### Oil-Free Compressor

- Suitable for all commonly used refrigerants

### Large Backlit Display

- Easy-to-read large LCD display
- Backlit for clarity

### Purge Function

- Prevent mixing of various refrigerants

### Twin Cylinder with 2-Row Oversized Condenser

- Fast recovery

Model		NRDD			
Refrigerant Type		Category III: R-12, R-134a, R-401C, R-500 Category IV: R-22, R-401A, R-401B, R-402B, R-407C, R-407D, R-408A, R-409A, R-411A, R-411B, R-412A, R-502, R-509 Category V: R-402A, R-404A, R-407A, R-407B, R-410A, R-507			
Power Supply	V / Hz	115V / 60Hz			
Motor	HP	1			
Max Current Draw	A	10			
Compressor		Oil-less, Air-cooled, Piston style			
Automatic Safety Shut-Off		558 psi / 38.5 bar			
Recovery Rate	lbs / min		R-22	R-134a	R-410a
		Direct Vapor	0.55	0.37	0.49
		Direct Liquid	6.88	5.34	7.98
		Push/Pull Liquid	14.2	11.00	15.1
Full Load Amps	A	11			
Dimension	in	16" x 10" x 14"			
Weight	lbs	25.4			

**2-YEAR WARRANTY**