NSW-661PC Mini LED Step Light with Photocell **Horizontal and Vertical Louvered Face**

Lamp: 1.08 Watts LED Source

PRODUCT DESCRIPTION

Nora's Mini LED Step Lights with an integrated Photocell use the latest in technology in solid state lighting. The energy saving photocell allows the step lights to turn on in the evening and off in the morning. Mini Step Lights are available with louvered or lensed face and can be easily installed in a standard single gang switch box. Louvered units include both a horizontal and vertical louver.

CONSTRUCTION

Mounting

Easily installs in a standard single gang switch box.

9 LEDs for a total of 1.08 Watts (0.12W each) Color Temp: 3000K

LED Driver

120VAC, 50/60Hz

 $\frac{\mbox{Wiring}}{\mbox{Standard wire nuts (not included). \#18AWG, rated 105°C 300V.}$

Photocell sensor comes pre-installed onto the step light's face. The energy savings dusk to dawn feature turns the LEDs on in the evening and off in the morning.

Louvered units include both a horizontal and vertical louver, so the step light can be mounted horizontally or vertically.

Brushed Nickel, Primer (ready to be painted), and White

Hallways, entrances, stairways, wall bases, or any application requiring a low profile, recessed fixtures providing safe illumination in indoor dark areas.

Labels and Listings

UL and cUL Listed for Wet Location





ENORALIGHTING.


Type

Project

Catalog No.

Lamp/Wattage

DIMENSIONS



Face Width: 4-1/2"

Housing Width: 3-5/8"

Housing Length: 1-1/2" Face Length: 2-3/4" Housing Depth: 1-1/8"

Example: NSW-661PC/W Create a complete step light catalog number:

Sten Light - select finish

otop zigitt seieet iiiisii	
Catalog No.	Finishes
NSW-661PC	BN = Brushed Nickel
	P = Primer
	W = White

