

QUALITY PRODUCTS FOR AIR CONDITIONING, REFRIGERATION & HEATING



Nu-Calgon Nu-Calgon Nu-Calgo

FASTEST, STRONGEST SEALANT ON THE MARKET

EasySeal Ultimate:

- Permanently seals even larger leaks
- Rapid Fusion Technology for a stronger bond
- Easiest to install direct inject
- Works with all refrigerants
- Treats larger systems
- New brighter UV dye





Table of Contents

Total System Protection	1-3	
Coil Cleaners and Sprayers	4-10	
Indoor Air Quality	11-15	
Gas Leak Detectors	16	
Refrigeration Oil & Vacuum Pump Oil	17-18	
Aerosol Products	19-21	
Specialty Products	22-23	
Insulation Products	24	
Glycol & Closed Systems	25-26	
Water Treatment & Plumbing Products	27-31	
Water Filtration Maintenance	32	
Everpure®	33-37	
Water Filtration	38-39	
Training Classes	40	

THE ULTIMATE IN REFRIGERANT LEAK SEALANTS













EasySeal® Ultimate

The EasySeal® line has proven to be the number one trusted leak sealant brand for years, with millions of leaks sealed. Now Nu-Calgon has made EasySeal even better with EasySeal Ultimate – the strongest and fastest leak sealant on the market, now with the ability to treat systems up to 10 tons in one application. EasySeal Ultimate features Rapid Fusion Technology™ for a stronger bond and a new injector design for easier installation. The UV dye versions – now with brighter UV dye – allow you to see where larger leaks are with the use of a UV light.

EasySeal Ultimate LS	Systems 2-10 tons	4050-08
EasySeal Ultimate LS/UV	Systems 2-7.5 tons (with UV dye)	4050-11
EasySeal Ultimate SS	Systems up to 2 tons	4050-05
EasySeal Ultimate SS/UV	Systems up to 2 tons (with UV dye)	4050-21
LS Bulk 6-Pack	Systems 2-10 tons	4050-07
LS/UV Bulk 6-Pack	Systems 2-7.5 tons (with UV dye/UV flashlight)	4050-12
UV Leak Detection Kit	UV flashlight and glasses	4050-15











A/C EasySeal®

A/C EasySeal prevents and seals refrigerant leaks in residential and light commercial ACR systems. It is perfect for those hard-to-find and expensive-to-fix leaks and works with all refrigerants (except ammonia). It is easily installed with the reusable piercing valve and hose. A/C EasySeal circulates with the system's refrigerant, and if a leak should occur, it will quickly and permanently seal the leak and prevent the system from losing refrigerant and shutting down.

A/C EasySeal	Pressurized can - treats 1.5 to 5 ton systems	4050-06
A/C EasySeal-SS	Pressurized can - treats fractional to 1.5 ton systems	4050-01
"2+1" Display Pack	2 cans of A/C EasySeal and an A/C Piercing Valve and Hose	4050-02
A/C EasySeal-XL	Treats systems with refrigerant charge of 125 lbs. to 250 lbs.	4050-10
A/C Piercing Valve and Hose	Use with A/C EasySeal and A/C EasySeal-SS	4051-99



Endorsed by York®, Goodman®, Nordyne®, Coleman®, and Daikin®







R_x11-flush®

R_X11-flush is a unique solvent engineered specifically for flushing refrigeration and air conditioning systems. R_X11-flush is ozone-safe, non-toxic, and non-flammable. Its patented HFC-based solvent formulation is powerful enough to flush away sludge, carbon residues, oils, acids, water and other particulates. Rx11-flush is ideal for system flushing after burnouts, during retrofits, and for flushing line sets for R-410A conversions. R_X11-flush has been the industry's standard for over a decade, and contractors agree — it's the best flush for R-410A retrofits and after compressor burnouts.

Rx11-flush Starter Kit	Contains a 1 lb. canister, Rx11-flush Gun and Hose, and Injection Valve	4300-08
1 lb. canister	Flushes 1-2 line sets	4300-09
"2+1" Display Pack	Contains one Injection Valve and two 2 lb. canisters	4300-10
2 lb. canister	Flushes up to 5 line sets	4300-11
13 lb. canister	Recommended for up to 50 ton system or 30+ line sets	4300-15
26 lb. canister	Recommended for systems over 50 tons or 60+ line sets	4300-26





R_X11-flush Liquid is a unique solvent engineered specifically for flushing refrigeration and air conditioning systems. It remains a constant boiling solvent, and its stronger, faster-acting formula dissolves more oil, moisture, and contaminants than any other flush. It is ideal for line sets, burnouts, and other flushing requirements.

19.5 ounce can	4300-30
Rx11-flush Liquid Starter Kit	4300-38



R_X11-flush[®] Accessories

The R_X11 -flush product family also includes various support tools. This includes the Injection Valve for hooking up to a charging hose for flushing and the Flushing Tool for facilitating line set flushing. In addition, the R_X11-flush Gun with a built-in flushing attachment and the R_x11-flush Hose (24") are available.

Flushing Tool	4300-50
Rx11-flush Gun	4300-51
Rx11-flush Hose (24")	4300-52
Injection Valve	4300-89

(Injection Valve fits Pneu-flush® and pressurized Rx-Acid Scavenger® as well)

Total System Protection



of older systems. It can also assist in oil return with R-22 replacement refrigerants. It's available in a quick, injectable treatment (using the Connect Injector Tool) or in a four-ounce can to be used with the A/C Re-New Injector Tool.

1 quart can	4057-54
4 fluid ounce can	4057-55
A/C Re-New Injector Tool	4057-99
A/C Re-New Connect Inject	4057-56
Connect Injector Tool	4155-01



Rx-Acid Scavenger®

The most effective way to neutralize or "scavenge" acid in refrigeration and air conditioning systems. Rx-Acid Scavenger is perfect for use after burnouts or during normal on-going system maintenance. In addition, Rx-Acid Scavenger can be used with all lubricants: mineral, alkylbenzene, and polyol ester. Now available in a pressurized can for easy injection into charged systems or hermetically sealed systems. Connect Inject version is a quick, injectable treatment that uses the Connect Injector Tool.

2 fluid ounce unpressurized bottle	4301-02
3.8 ounce pressurized can	4301-05
Injector Valve	4300-89
Rx-Acid Scavenger Connect Inject	4301-06
Connect Injector Tool	4155-01

(Injection Valve fits R_X11-flush® and Pneu-flush® as well)

A/C ReStart™

A/C ReStart is a POE lubricant treatment designed specifically for R-22 retrofits. It eliminates oil change-out by boosting oil return. A/C ReStart also includes Rx-Acid Scavenger for addressing trace acids during retrofits. It's available in a quick, injectable treatment (using the Connect Injector Tool) or in a four-ounce can to be used with the A/C Re-New Injector Tool.

4 fluid ounce can	4060-55
A/C ReStart Connect Inject	4060-56
Connect Injector Tool	4155-01



Phase III® Refrigeration Oil Acid Test Kit

Formulated for use with POEs as well as mineral oils and alkylbenzene, Phase III is an inexpensive, disposable test kit that provides proof-positive that acid level in refrigeration oil is either safe or unsafe. Phase separation makes it easy to see change in color of acid indicator (even if a leak detection dye has been added to the oil). With just two bottles to use, it is simple, safe, accurate, and small enough that you can carry several in your tool box.

1 each	4320-W8
--------	---------

TOTAL SYSTEM PROTECTION

Nu-Calgon Coil

Cleaners Found on Pages 6-9

Nu-Calgon Coil



				EQUIP	MENT USEI	D ON				
Condenser Coils	•	•	•	•	•	•	•	•	•	•
Mini-Split Condenser Coils						•	•	•	•	•
Small Condenser Coils	•	•	•	•	•	•	•	•	•	•
Evaporator Coils					•	•	•	•		
Mini-Split Evaporator Coils						•	•	•		
Small Evaporator Coils					•	•	•	•		
Microchannel Coils						•	•	•	•	•
Electronic Air Filters								•		
Fan Blades, Permanent Filters					•	•	•	•	•	•
				FORMULA	TED TO F	REMOVE				
Greasy Dirt & Oil	•	•	•	•	•	•	•	•	•	•
Cooking Grease	•	•	•	•		•		•		•
Lint, Dust, Dirt & Grime	•	•	•	•	•	•	•	•	•	•
Tobacco Tars								•		
Oxide (Corrosion) Deposits	•		•	•	•					
Cottonwood/ Bugs		•	•	•	•			•		
				FEATUF	RES & BENI	EFITS				
Product Type	Alka		Alkaline	Alkaline	Acidic	Alkaline	Alkaline	Alkaline	Alkaline	Alkaline
Foaming	Aerosol	Liquid	•	•	•					
Brightening	•	•	•	•	•					
Degreasing	•	•	•	•	•	•	•	•	•	•
EPA Registered Disinfectant										
No Rinse (Evaporators)						•*	•*	•*		
No Rinse (Condensers)										•
Biodegradable	•	•	•	•	•	•	•	•	•	•
USDA Authorized	•	•					•	•		
U.S. EPA's Safer Choice										
NSF Registered		•	•	•		•			•	

Cleaners Found				0	101	Arms Care Clean	2 ===	• 55		
on Pages 6-9	Evap-Pow'r®-C	Evap-I	resh® †	Cal-Green™	Evap-Green™	Green Clean	Evap-Foam®	Blackhawk®	Nu-Blast®	Cal-Blast®
	Ziap rom r o	No F	linse	Odir Groom	Evap directi	di doli didali	Evap i dam	Didoktidatik	No Black	our Black
	v			EQUIP	MENT USE	D ON	Ť		Ť	Ť
Condenser Coils				•		•		•	•	•
Mini-Split Condenser Coils				•		•		•	•	•
Small Condenser Coils				•		•		•	•	•
Evaporator Coils	•	•			•	•	•	•		
Mini-Split Evaporator Coils	•	•	•		•	•	•	•		
Small Evaporator Coils	•	•			•	•	•	•		
Microchannel Coils	•	•	•	•	•	•	•	•	•	•
Electronic Air Filters										
Fan Blades, Permanent Filters	•			•	•	•	•	•	•	•
			F	ORMULA	TED TO F	REMOVE				
Greasy Dirt & Oil	•			•	•	•	•	•	•	•
Cooking Grease								•	•	•
Lint, Dust, Dirt & Grime	•	•	•	•	•	•	•	•	•	•
Tobacco Tars										
Oxide (Corrosion) Deposits										
Cottonwood/ Bugs										
				FEATUR	ES & BEN	EFITS				
Product Type	Alkaline		ıline	Alkaline	Alkaline	Alkaline	Alkaline	Alkaline	Solvent	Alkaline
Foaming		Aerosol	Liquid				•	•		
Brightening										
Degreasing						•		•	•	•
EPA Registered Disinfectant		•	•							
No Rinse (Evaporators)	•	•	•		•	•*	•	•		
No Rinse (Condensers)									•	•
Biodegradable	•	•	•	•	•	•	•	•		
USDA Authorized	•									
U.S. EPA's Safer Choice				•	•					
NSF Registered							•	•		

† Product not registered for sale in Canada.

COIL CLEANER SELECTION GUIDE

^{*} Dilution ratios for no rinse applications: Tri-Pow'r HD = 10:1, Liquid CalClean = 10:1, Special HD CalClean = 40:1, Green Clean = 10:1





Nu-Brite®

Nu-Brite is the most effective coil cleaner available today. It foams, brightens, and cleans more effectively than acids, particularly in removing grease. Biodegradable. The liquid versions are USDA approved and NSF registered.

18 ounce can	4291-18	
1 gallon bottle	4291-08	
2.5 gallon pail	4291-05†	(NSE)
55 gallon drum	4291-01	
4x concentrate 1 quart*	4291-90	

^{*} Use with CleanConnect Sprayer (4773-0)



Foam-Brite®

The ultimate in foaming alkaline cleaners, Foam-Brite cleans and brightens while at the same time providing tremendous foaming to push dirt and grime out of the coil. Can easily be used in place of the more dangerous HF acid-based products. Biodegradable. NSF registered.

1 gallon bottle	4178-08	
2.5 gallon pail	4178-05†	(NSF)
55 gallon drum	4178-01	



Alka-Brite® Plus

A non-acid, alkaline based product for brightening and cleaning air-cooled condensers, Alka-Brite Plus contains the best available detergents to quickly penetrate and remove oxidation. Its foaming action helps to lift greasy soils out of the coil. Biodegradable. NSF registered.

1 gallon bottle	4120-08	
2.5 gallon pail	4120-05†	ISF.
55 gallon drum	4120-01	191
4x concentrate 1 quart*	4120-90	

^{*} Use with CleanConnect Sprayer (4773-0)



Cal-Brite® Plus

Cal-Brite Plus is a low pH cleaner developed for cleaning evaporator coils, air-cooled condensers, and other finned cooling and heating coils. Its versatility is based upon a synergistic acid formulation and other unique ingredients. It provides moderate foaming and brightening and is safe for use indoors as well as outdoors. It's particularly suitable when lime scale must be removed from outdoor coils.

1 gallon bottle	4133-08
55 gallon drum	4133-01

†A 2.5 gallon pail wrench is also available. Part Number ZE64.



Tri-Pow'r® HD

Tri-Pow'r HD is an outstanding general purpose coil cleaner, providing detergency and degreasing as well as deodorizing capability. Its positive emulsion technology is very effective against oily grime as it converts the deposits into a more liquid form that can be easily rinsed. It is non-acid, non-toxic, and biodegradable. NSF registered. Also great for microchannel coils.

19 ounce can	4371-75	
1 gallon bottle	4371-88	(NSF)
2.5 gallon pail	4371-86†	
55 gallon drum	4371-81	
4x concentrate 1 quart*	4371-90	

4135-08

4135-06†

4135-01





CalClean® CalClean is an alkaline detergent formulated for cleaning evaporator coils, air-cooled condenser coils, metal filters, fan blades, and other surfaces soiled with grease, dust and dirt. Biodegradable. USDA approved. Also great for microchannel coils. 1 gallon bottle

55 gallon drum Special HD CalClean® The best non-foaming cleaner available, Special HD CalClean is specifically formulated to remove tobacco tars from electronic air cleaners as well as the most stubborn deposits from finned coils. USDA approved. Also great for microchannel coils.








2.5 gallon pail

1 gallon bottle 4143-08 2.5 gallon pail 4143-06† 55 gallon drum 4143-01

Evap Pow'r®-C



1 gallon bottle	4168-08
2.5 gallon pail	4168-05†
55 gallon drum	4168-01


[†] A 2.5 gallon pail wrench is also available. Part Number ZE64.

TriClean 2x™

The new way to clean a condenser coil. Simply connect to hose, clean, and rinse. TriClean 2x is metal-safe, designed for rapid emulsion of soils from the coil. Restores efficiency and is ideal for painted fin and microchannel coils. Eliminates the need for a sprayer.

1 quart sprayer with hose c	onnector	4372-24	()	NSF	

Nu-Solve™ NR



1 gallon bottle	4295-08	



CLEANERS

COIL

(NSF)

^{*} Use with CleanConnect Sprayer (4773-0)



Evap Foam No Rinse®

Evap Foam No Rinse is a high-performing, heavy-duty detergent. It is formulated with special surfactants and alkaline cleaners that have been developed into a foaming, no-rinse product. Evap Foam is ideal for use on most coils, but it is particularly suited for use on cooling or evaporator coils. The aerosol can be sprayed either right side up or upside down. NSF registered. Can be used with Talon Flexible Aerosol Wand (4776-0) for hard to reach locations (see page 19).

18 ounce can	4171-75	(N	ISE	



Evap-Fresh® No Rinse Evaporator Coil Cleaner & Disinfectant†

Evap-Fresh is a ready-to-use, no-rinse cleaner and disinfectant for evaporator coils. It effectively cleans, as well as controls, mold and bacteria. This one-step no-rinse disinfectant cleaner is perfect for air conditioners, commercial air handling units, HVAC cooling coils, refrigeration equipment, and evaporator coils. EPA registered specifically for use on HVAC equipment. Aerosol can be used with Talon Flexible Aerosol Wand (4776-0) for hard to reach locations (see page 19).

18 ounce can	4166-75
1 gallon bottle	4166-08



Green Clean

Green Clean is a pleasantly scented, all-purpose, environmentally friendly cleaner designed for the rapid removal of grease and other heavy soils on coils and other surfaces. It can be used right out of the bottle or diluted for milder jobs. Biodegradable. Also great for microchannel coils.

1 quart spray bottle	4186-24
1 gallon bottle	4186-08
55 gallon drum	4186-01

The following products are part of Nu-Calgon's Environmentally Friendly Green Select line. These coil cleaners meet the U.S. EPA Safer Choice Program standards, making them a safer choice for the user and the environment.





Cal-Green™ Condenser Cleaner

Cal-Green is a plant-based, natural condenser cleaner that is powerful enough to remove dirt, grease, and grime. It meets the U.S. EPA Safer Choice Direct Release Program standards, making it a safer choice for the user and the environment. This non-foaming, non-toxic concentrate is perfect for cleaning residential or commercial systems and restores their efficiency while being environmentally responsible. Also OEM approved for microchannel coils.

1 gallon bottle	4190-08
55 gallon drum	4190-01





Evap-Green™ Evaporator Cleaner

Evap-Green is a no-rinse product that is perfect for numerous heating and air conditioning applications, such as evaporator coils, roof top units, window units, metal filters, fan blades, and more. Evap-Green meets the U.S. EPA Safer Choice Direct Release Program standards, making it a safer choice for the user and the environment. It is also biodegradable and will not harm plants, animals, or aquatic life. Metal-safe — meets OEM guidelines for all aluminum coils, including microchannel types.

1 gallon bottle	4191-08
55 gallon drum	4191-01

+ Product not registered for sale in Canada.

Coil Cleaners



Blackhawk®

Blackhawk is an expanding foam coil cleaner formulated to deeply penetrate the coil. It liquefies to quickly remove grease, grime, or oily soils from deep within the coil. Blackhawk's formulation is safe and problem-free for cleaning evaporator or condenser coils in an occupied building; produces no objectional fumes. It is particularly effective on coils on refrigerators, coolers, and freezers located in restaurants and other commercial establishments. NSF registered. Can be used with Talon Flexible Aerosol Wand (4776-0) for hard to reach locations (see page 19).

18 ounce can 4127-75





Nu-Blast®

Nu-Blast is a no-rinse condenser coil cleaner in a convenient aerosol package. Double action of highpressure blast and solvent cleaning restores design efficiency of condenser coils. It is non-flammable and non-conductive. No rinse required — cleaning solvent evaporates completely. Use with adequate ventilation. Not for sale in California.

18 ounce can	4290-75
--------------	---------



Cal-Blast®

Cal-Blast is a no-rinse condenser cleaner that will powerfully separate undesirable materials from the surface, offering maximum cleaning of finned coils. It's a high-performance aerosol with excellent solvency and blasting spray. Not for sale in California.

20 ounce can	4132-20

Coil Protectants



DuraCoil™

DuraCoil is a long-lasting coating for coils and surfaces in corrosive environments. It uses a durable, OEM-approved Heresite® coating. DuraCoil has a fast, air-dry formula that bonds to all metals and causes negligible heat transfer loss across the coil. Great for repairing an OEM-approved coil coating that has been compromised while in service! Brown in color.



Cal-Shield®

Cal-Shield is a synergistic fluoro-additive liquid formulation pretreatment of the coil for special duty circumstances. It's designed for application on air-cooled condensers, evaporator coils, and other finned heating and cooling coils. Cal-Shield will shield and protect the coil from adverse conditions.

•	1 quart spray bottle	4148-32
	1 gallon bottle	4148-08

COIL CLEANERS

Clean Connect™ Sprayer

Clean Connect™ Sprayer easily connects to Nu-Calgon's 4x Concentrate Coil Cleaners (Nu-Brite 4x, Alka-Brite Plus 4x and Tri-Pow'r HD 4x). There's no need to pour any coil cleaner, preventing any spilling from occurring. The sprayer regulates the dilution of coil cleaner with water to make coil cleaning easier than ever! The Clean Connect Sprayer comes with a carrying bag and accessory to hook up the Nu-Calgon Probe (4774-1) extension spray wand available separately.

4773-0 1 each



Coil Gun®

Coil Gun is a "hose-end" sprayer that features five different mix ratio settings designed for coil cleaners. Utilizes a 2 quart capacity bottle and includes a foam wand as well as "quick disconnect" capability. The Coil Gun Probe accessory has a 90° direction of spray that allows cleaning from inside the coil. It also provides easy access in tough-to-reach locations.

Coil Gun	4774-0
Coil Gun Probe	4774-1



Coil Mate™ Coil Cleaning Hose

Durable 5/8 inch diameter reinforced hose with Flex-Guard protection. The 50-foot hose is equipped with solid brass wrench fittings. The Coil Mate is a necessity when using the popular Coil Gun® or rinsing an air-cooled coil with water after using a Nu-Calgon coil cleaner.

Coil Mate Hose	61231
Hot Water Hose	61238
Plastic Pistol Grip Nozzle	61241



Nu-Solve NR Sprayer

Backpack-type sprayer developed for applying Nu-Solve NR, a no-rinse outdoor coil cleaner when water availability for rinsing is an issue. Sprayer utilizes a four-gallon tank with no holes or connections at the bottom to leak!

1 each	4775-0
--------	--------












POLY SPRAYERS				
Model	Construction	Capacity	Features	Part #
No. 50P	High-density translucent polyethylene	3 pints	Plastic adjustable nozzle	4770-0
No. 100P	High-density translucent polyethylene	1 gallon	Brass wand & adjustable nozzle	4770-2
No. 200P	High-density translucent polyethylene	2 gallons	Brass wand & adjustable nozzle	4771-2
No. 220CP	High-density translucent polyethylene	2 gallons	Plastic wand & adjustable nozzle	4771-3
No. 300P	High-density translucent polyethylene	3 gallons	Brass wand & adjustable nozzle	4772-0
Multi-purpose Sprayer	Plastic bottle with trigger sprayer	24 ounces	Bottle marked for dilutions	4768-W3



Breathe cleaner, fresher air!

With the technology installed in over 100,000 applications worldwide, iWave is a complete line of bi-polar, high-output ion generators designed specifically for treating air in air conditioning systems. As the air flows past the iWave, positive and negative ions actively purify the supply air,



DIRTY AIR

* Visit iwaveair.com to learn more.

iWave®-R Residential Air Cleaner

- Patent-pending self-cleaning design, no maintenance needed
- For duct systems up to 6 tons (2400 CFM)
- Universal voltage 24VAC to 240VAC
- Universal mounting
- Programmable cleaning cycle with integral alarm contact
- No replacement parts needed

1 each	4900-20

iWave®-C Commercial Air Cleaner

- Patent-pending self-cleaning design, no maintenance needed
- Duct-mount install for systems up to 12 tons (4800 CFM)
- Waterproof housing for installation inside or outside
- Universal voltage 24VAC to 240VAC
- · Programmable cleaning cycle with integral alarm contact



iWave®-M Mini-Flexible Air Purifier for Ductless Systems

- Versatile ion needles mounted in a flexible bar circuit
- For HVAC cooling coils up to 36" wide
- For ductless systems (mini-split, PTAC) and ice machines
- · Chemical and temperature resistant, durable for long service life
- Voltage input 110VAC to 240VAC

1 oach	4000-35

iWave®-F Flexible Air Cleaner

- Versatile ion needles mounted in a flexible bar circuit
- For HVAC cooling coils up to 48" wide
- For ductless systems (mini-split, PTAC), duct systems and ice machines
- Durable bar is chemical and temperature resistant
- Voltage input 110VAC to 240VAC

1 each	4900-30

iWave®-V Residential Air Cleaner

- Low maintenance air purifier
- For systems up to 6 tons (2400 CFM)

1 each

- · Universal mounting with integrated
- magnets
- Small compact design with no replacement parts
- Voltage input 24VAC














INDOOR AIR QUALITY













The Original ClenAir™ Odor Neutralizer

ClenAir's unique odor neutralizing formula removes odors quickly and permanently. It is a true odor eliminator, not a mask. Originally designed for use in central air systems, on fire and flood restoration jobs and in sewage facilities, ClenAir is a professional product, yet it leaves no lingering antiseptic or perfume smell. It is great for odors caused by fuel oil, smoke, pets, mold and mildew, cigarette and cigar smoke, decay, cleaning solvents, and even skunks. ClenAir has three different scents: Original, CherryAir, and OrangeAir. The scents come in multiple sizes for multiple applications.

Nu-Calgon	ClenAir
61000	CA1500M
61001	1500D
61002	1500
61003	1501
61004	1503
	61000 61001 61002 61003

Original	Nu-Calgon	ClenAir
10 lb. Tub	61005	1510
30 lb. Tub	61006	1530
Wall Unit (White)	61007	1300
Gel Brick for Wall Unit (1lb.)	61008	1401

CherryAir	Nu-Calgon	ClenAir
Mini Tub	61018	CA1800M
1/2 lb. Tub display box	61010	1800D
1 lb. Tub	61011	1801
OrangoAir	Nu Calgan	

3 lb. Tub	61023	CA1303
OrangeAir	Nu-Calgon	ClenAir
30 lb. Tub	61017	1830
10 lb. Tub	61015	1810
3 lb. Tub	61013	1803

61025

61027

CA1310

CA1330

Mini Tub 61028 CA1300M 1/2 lb. Tub display box 61020 CA1300D 1 lb. Tub 61021 CA1301

HVAC Odor Block®

ClenAir HVAC Odor Block is not a perfume mask or cover-up. The unique ClenAir formula molecularly reacts with the airborne odor-causing compounds and eliminates them and other indoor pollutants, leaving clean, fresh air behind. The HVAC Odor Block makes it easy to remove odors and improve the indoor air quality in the entire home or building by treating the air through the HVAC system. Use in A/C units, furnaces, rooftop units, fan coil units, and air handlers. Part numbers 61060 and 61061 last up to 3 months. The HVAC Odor Block XL (61070) lasts up to 6 months.

10 lb. Tub

30 lb. Tub

	Nu-Calgon Number	ClenAir Number
Residential HVAC Odor Block	61060	1502
Residential HVAC Odor Block XL	61070	
Commercial HVAC Odor Block	61061	CA1015

The ClenAir MiniFresh eliminates odors caused by mold, mildew, bacteria, pets, smoke, water damage, fire damage, paints, chemicals, stale air, and more! The unique ClenAir formula molecularly reacts with the airborne odor-causing compounds and eliminates them and other indoor pollutants leaving clean, fresh, air behind. Use in mini split, PTAC, or other ductless systems. The MiniFresh can be installed on the return louvers of indoor units. It will be out of view and will work quietly to eliminate odors. MiniFresh mini split odor eliminator treats up to one 12,000 BTU indoor unit for 3 months.

MiniFresh	61065

ClenAir Liquid Formula

ClenAir Liquid is a fast acting deodorizing product. It eliminates odors via an oxidation process while leaving a fresh scent. Applications include HVACR equipment, such as evaporator coils, duct work, condensate pans, refrigeration cases, reach-ins, and walk-in boxes. It can also be poured down drains, garbage disposals, and in trash cans. Spray in restrooms, locker rooms, and on fouled carpeting and upholstery. Used by hospitals, nursing homes, and HVACR technicians.

	Nu-Calgon	ClenAir
Unscented Spray 16 oz.	61030	1600D
Unscented Liquid 1 gal.	61031	1610
Citrus Spray 16 oz.	61033	1700D

	Nu-Calgon	ClenAir
Citrus Liquid 1 gal	61035	1710
CherryAir Spray 16 oz.	61037	1900D
CherryAir Liquid 1 gal.	61038	1910

Indoor Air Quality





PanPads[†]

Pan-Treat®

PanPads are formulated to eliminate the build-up of bacteria and slime growth in air conditioning and refrigeration condensate drain pans. In laboratory tests, they have been proven effective against a wide spectrum of harmful bacteria, including Legionella. The product is EPA registered for this application. NSF registered.

5 (up to 5 tons)	4295-34 NSF	15 (up to 15 tons)	4296-24 NSF
5 Slim (up to 5 tons)	4295-36 NOT	45 (up to 45 tons)	4296-45 NOT



Pan-Treat condensate tablets control odors and prevent overflows caused by plugged condensate drain lines. They can also be used in humidifiers. They are very easy to use, as well as non-corrosive, non-toxic, and biodegradable.

1 bottle (200 tablets)	4296-60
------------------------	---------

PurCool® Green Strips and Tablet

PurCool Strips/Tablets prevent sludge, odors, and overflow of condensate pans. Time release formula adheres to pan and fully dissolves over time. PurCool Green Strips/Tablets use plantbased suspending and dispersing action to keep drain pans clean and free flowing. Products are available for commercial, residential, and mini split applications. Sizes are based on system tonnage, with each strip/tablet lasting up to six months. Biodegradable and environmentally friendly. Will not harm aquatic life.

<u> </u>		
	Nu-Calgon Number	ClenAir Number
PurCool Green Mini Strip	61044	PCG5MS
PurCool Green Commercial Strip 10 ton	61045	PCG10T
PurCool Green Commercial Strip 30 ton	61046	PCG30T
PurCool Green 3 ton tablet	61048	
PurCool Green 3 ton bulk (200)	61049	
PurCool Green 5 ton tablet	61051	PCG5T
PurCool Green 5 ton bulk (100)	61052	PCG5T-100

+ Product not registered for sale in Canada.



INDOOR AIR QUALITY

15

INDOOR AIR QUALITY



PurCool® Strips

PurCool Strips keep A/C and refrigeration condensate drain pans clean and free flowing. Use PurCool Strips to prevent condensate drain clogs, costly overflows, and corrosion. Just place them anywhere in the drain pan where the PurCool Strip will contact the condensate water and enjoy up to six months of economical protection. PurCool Strips will adhere to the drain pan and will not float or move. Dissolves completely, leaving no residue. Safe for metal and plastic drain pans.

	Nu-Calgon	ClenAir
3 ton strip	61043	1903D
3 ton strip bulk (100)	61047	1903D-100
5 ton strip	61042	2001D

	Nu-Calgon	ClenAir
10 ton strip	61041	2003D
30 ton strip	61040	2009

urCoo

PurCool® Tablets

PurCool Tablets utilize a powerful formulation to keep condensate drain pans clean and free flowing. Use PurCool Tablets to remove sludge and slime in A/C condensate pans to prevent costly water damage caused by overflows. They will control clogs, build-up, odors, and corrosion in drain pans, condensate pumps, and humidifiers.

	Nu-Calgon Number	ClenAir Number
1 bottle (200 tablets)	61053	PC200



HVAC Carbon Block® In-Duct Air Purification System

HVAC Carbon Block is an add-on carbon purifier for all HVAC systems. Improves indoor air quality by removing odors, indoor air pollutants, and VOCs. Treats up to 10 tons for up to nine months.

	Nu-Calgon Number	ClenAir Number
HVAC Carbon Block	61062	CACB10



Humidifier Panel™ Replacements

ClenAir Universal Humidifier Panels provide optimum moisture output, performance, and durability. They replace Aprilaire, Honeywell, Carrier, Bryant, Lennox, ICP, and others. Ultra Upgrade Humidifier Panels' material retains water, increasing moisture output and reducing water waste by up to 50%. They replace Aprilaire, Honeywell, Carrier, Bryant, Lennox, ICP, and others.

	Nu-Calgon Number	ClenAir Number
Universal Humidifier Panel - #10 size	61250	CA10
Universal Humidifier Panel - #12 size	61251	CA12
Universal Humidifier Panel - #35 size	61252	CA35
Ultra Upgrade Humidifier Panel - #10 size	61254	CA10UP



Spacegard® Filter Media Replacements

Visit us at www.nucalgon.com or call 1-800-554-5499

These Merv 11 filter media are direct replacements for the Aprilaire Spacegard 201 and 401. Merv 11 media removes pollen, allergens, smoke, dust, dust mites, bacteria, spores, and pet dander. The large filter surface area provides for low resistance and longer filter life - more than 6 months!

	Nu-Calgon Number	ClenAir Number
Replacement for Aprilaire Spacegard 201	61256	CA201
Replacement for Aprilaire Spacegard 401	61257	CA401

*Aprilaire and Spacegard are registered trademarks of Research Products Corporation

Indoor Air Ouality



Evap-Fresh® No Rinse Evaporator Coil Cleaner & Disinfectant†

Evap-Fresh is a ready-to-use, no-rinse cleaner and disinfectant for evaporator coils. It effectively cleans, as well as controls, mold and bacteria. This one-step, no-rinse disinfectant cleaner is perfect for air conditioners, commercial air handling units, HVAC cooling coils, refrigeration equipment, and evaporator coils. EPA registered specifically for use on HVAC equipment to disinfect H1N1 and other viruses such as Norwalk, Rhoto, Hepatitis, Rabies MRSA, and more. Talon spray wand (4776-0) can be used with aerosol to reach tough locations.

18 ounce can	4166-75
1 gallon bottle	4166-08



Clean Guard™ Mini-Split Bag

Clean Guard is a professional mini-split maintenance bag that protects walls and flooring from cleaning solutions when cleaning the indoor coil. It installs in seconds, with an elastic collar that snaps around the unit. Product offers 360-degree coverage with an eight-foot drain line. Heavy duty plastic can be reused on repeated maintenance calls.

Clean Guard – units up to 12,000 BTU	4150-01
Clean Guard XL – units 18,000 to 36,000 BTU	4150-02
Clean Guard CC Commercial Ceiling Cassettes	4150-03



Bio-Fresh® cd†

A ready-to-use bacteriostatic, fungistatic, and deodorizer based upon chlorine dioxide technology. Inhibits the growth of bacteria, mold, mildew, fungi, and yeasts in IAQ applications, and it may be applied to occupied spaces. EPA registered for use in HVACR ventilating equipment, including coils, condensate pans, filters, and duct-work. Easily applied by spraying, brushing, sponging, or wiping. Use Bio-Fresh Fogger for spraying in duct work and large areas.

1 quart spray bottle	4126-34
1 gallon bottle	4126-38
Bio-Fresh Fogger	4693-0



Drain Solve

Ideal for condensate pan drains, Drain Solve saves time and money with its ease of use. It eliminates application concerns associated with more reactive, fuming drain openers. Simply pour it down the drain and let it work without fear of noxious fumes or reactions. Does not contain sulfuric acid.

1 quart	4165-24	ALOS I
1 gallon	4165-08	(NSF)
55 gallon drum	4165-01	



A/C Drain Sucker®

A/C condensate drain pan overflow is caused by slime and sludge that builds up and clogs the drain line. The A/C Drain Sucker quickly removes the clog and the excess water, resolving the overflow problem. The kit includes a PurCool® Green 3 ton tablet to provide months of preventive treatment and free flowing drains, as well as all fittings and hoses for suction or pressure applications.

	Nu-Calgon Number	ClenAir Number
A/C Drain Sucker kit	61308	CADS1
PurCool Green 3 ton tab	61048	

+ Product not registered for sale in Canada.

INDOOR AIR QUALITY

in contact with the applied surface for an extended period of time, allowing it to detect the smallest of leaks. The longest lasting bubbles in the industry! It is also non-corrosive to metal, and it will not affect ultraviolet or black lights. Now available in a non-aerosol pressurized container that can be sprayed at any angle! NSF registered.

6 ounce bottle with dauber	4182-53	
7 ounce pressurized spray	4182-35 NSF	
1 quart spray bottle	4182-24	
1 gallon bottle	4182-08	



Cal-Blue® LT Gas Leak Detector

The same high quality formulation as regular Cal-Blue Plus, but it has added freeze protection to -20°F. It is the ideal detector for geographical areas that may experience very cold temperatures. The longest lasting bubbles in the industry! NSF registered.

1 quart spray bottle	4183-24	NSE)
1 gallon bottle	4183-08	NOE



Gas Leak Detector

The original industry leak detector. A high viscosity liquid that forms bubbles when daubed on a gas leak. Non-corrosive, non-staining, and harmless to skin. Detects any type of gas leak, such as air, compressed air, carbon dioxide, nitrogen, natural gas, and refrigerant gases. Freeze protection to -20°F. Six ounce plastic bottles have dauber in cap. USDA approved.

6 ounce bottle with dauber	4180-53



Fluorescent Gas Leak Detector

A fluorescent formulation that provides improved visibility and long lasting bubbles. It is non-corrosive to metals and is freeze protected to 5°F. Suitable for high and low temperature applications. Can be used for most refrigerants, natural gas and oxygen systems. USDA approved.

8 ounce bottle with dauber	4184-53
1 quart spray bottle	4184-24
1 gallon bottle	4184-08



AccuTrak® Ultrasonic Leak Detector

Model VPE - Now with touchprobe included. Patented technology detects the ultrasonic sound of a leak!

	Nu-Calgon Number	ClenAir Number
AccuTrak® Ultrasonic Leak Detector	61307	CAVPE





Emkarate® POE Lubricants

The Emkarate family of polyol ester refrigeration lubricants are designed specifically for use with HFC refrigerants. They are available in a range of viscosities. They have excellent thermal and chemical stability, and they are compatible with a wide range of elastomers, polymeric materials, and other materials of construction. Fully miscible and compatible with mineral oils and alkylbenzene lubricants, as well as with CFCs, HCFCs, and HFCs.

Emkarate RL	Viscosity	1 Quart	1 Gallon	5 Gallon	53 Gallon
22H	100 SUS		4313-46		
32H	150 SUS	4314-44	4314-46	4314-45	4314-41
32HB	150 SUS			4314-62	
32-3MAF	150 SUS	4314-64	4314-66	4314-65	4314-67
46H	200 SUS		4315-46		4315-41
68H	300 SUS	4316-44	4316-46	4316-45	4316-41
68HB	300 SUS		4316-86	4316-85	
68HP	300 SUS		4316-76		4316-71
85HB	425 SUS		4316-91		
100E	500 SUS		4317-66		4317-61
100H	500 SUS		4317-46		
170H	850 SUS		4318-26	4318-25	4318-21
220H+	1100 SUS		4318-66	4318-65	4318-61
220XL	1100 SUS			4318-75	



C-3s, C-4s, C-5s Mineral Oil

These are mineral naphthenic lubricants manufactured by Calumet Lubricant Company and available in three viscosities. They are specifically designed for today's high performance air conditioning and refrigeration compressors using CFC and HCFC refrigerants. These compressors run at higher speeds and generate higher temperatures, and as a result, they require better lubrication. Use of these oils will ensure continued efficient operation.

Nu-Calgon	Viscosity	1 Gallon	5 Gallon	55 Gallon
C-3s	150 SUS	4303-07	4303-05	4303-01
C-4s	300 SUS	4304-07	4304-05	4304-01
C-5s	500 SUS	4305-07		4305-01



Zerol® Alkylbenzene Refrigeration Oil

Zerol Refrigeration Oil is recommended for use in all refrigeration and air conditioning applications using CFC and HCFC refrigerants. It is highly recommended by refrigerant and compressor manufacturers for use with R-22 and other HCFC blends such as R-409A as it provides many distinct advantages: excellent miscibility, excellent thermal stability, and low temperature performance compatibility with mineral oils. It is the oil of choice for R-22 and R-502.

Zerol	Viscosity	1 Gallon	5 Gallon	55 Gallon
150	150 SUS	4310-07	4310-05	4310-01
200TD	200 SUS	4308-07	4308-05	4308-01
300	300 SUS	4311-07	4311-05	4311-01
400CA	400 SUS		4311-65	
500	500 SUS		4312-05	

GAS LEAK DETECTORS

19



Idemitsu Polyvinyl Ether Lubricant

PVE lubricants provide for increased stability and lubrication. They do not hydrolyze in the presence of moisture, a very important feature in HVACR applications. Additionally, they are compatible with other refrigeration oils and process fluids. PVE lubricants also exhibit compatibility and performance with frequently used anti-wear additives.

Idemitsu	Viscosity	1 Quart
FVC32D	150 32 SUS	4319-14
FVC68D	300 68 SUS	4319-24



PAG Oil

Polyalkylene glycol (PAG) oil is a synthetic compressor lubricant used by OEMs for R-134a refrigerant and other specialty applications. It has outstanding lubricity and biodegradable properties, and recently has been FDA approved for use with equipment that may come in contact with food.

Zerol RFL-68EP	5 gallon pail	4316-95



Vacuum Pump Oil

Nu-Calgon's Vacuum Pump Oil is a quality, high-grade lubricant that performs at the deepest vacuum. It has a very low vapor pressure, and it has excellent lubricity for complete surface protection. It contains no additives or detergents.

1 pint bottle	4383-34
1 quart bottle	4383-24
1 gallon bottle	4383-07

Refrigeration Oil Products



Refrigeration Oil Charging Pump

An oil pump for charging refrigeration oil into a system, even while it's running. This pump can be used for 1 gallon, 2.5 gallon, and 5 gallon containers. Incorporates an automatic bleed valve that keeps pressure equalized inside the container and includes a tapered rubber adapter that fits all container openings without the need for additional adaptors.

1 each	4814-40



Total Lube Refrigeration Oil Test Kit

Visit us at www.nucalgon.com or call 1-800-554-5499

Have a professional lab analyze the oil to help detect potential problems such as metal wear or burnouts. The analysis will provide information on the oil's moisture, total acid number, viscosity, color, and spectrochemical analysis on 20 plus metals and compounds. Help prevent potential downtime, burnouts, and costly oil changes by incorporating regular testing of the refrigeration oil.

1 each	4996-0



Oil Refractometer

The Oil Refractometer is a precision optical instrument that allows for the rapid and accurate determination of the refractive index of oil solutions. It will specifically assist in determining the percent of residual oil remaining in a refrigeration system when converting it to a new refrigeration oil. Such retrofits require converting the mineral oil to a polyol ester (POE) or polyalkylene glycol (PAG), an alkylbenzene lubricant (Zerol®) to a POE, or a mineral oil to an alkylbenzene.

|--|



CanVerter®

Canverter is a hand-held pump used to remove or add oil to hermetic compressors. Easy to use; each stroke pumps 1 ounce of oil.

1 each	4814-0	

Aerosol Coil Cleaners



Blackhawk®

Blackhawk is an expanding foam coil cleaner formulated to deeply penetrate the coil. It liquefies to quickly remove grease, grime, or oily soils from deep within the coil. Blackhawk's formulation is safe and problem-free for cleaning evaporator or condenser coils in an occupied building; produces no objectional fumes. It is particularly effective on coils on refrigerators, coolers, and freezers located in restaurants and other commercial establishments. NSF registered. Can be used with the Talon Flexible Aerosol Wand (4776-0) for hard to reach locations.

8 ounce can	4127-75	(NSF)



Tri-Pow'r® HD

Tri-Pow'r HD aerosol provides a powerful foaming spray to assist in lifting debris off of coils. It's a detergent, degreaser and deodorizer - all in one convenient spray. Suitable for any coil design, including microchannel. Tri-Pow'r HD can be used for evaporator "no-rinse" applications where ample condensate will self-rinse the coil.

ounce can	43/1-/5	(112)



Nu-Brite®

Nu-Brite is a very effective degreaser and cleaner on condenser coils. Its high foaming characteristic will help push soil deposits out of the coil, leaving it clean and bright. With proper ventilation, it can also be used as a kitchen degreaser by emulsifying stubborn, resistive grease deposits found on coils located in kitchens. Product should be used where adequate rinsing is possible.

18 ounce can	4291-18
--------------	---------



Evap Foam No Rinse®

Evap Foam No Rinse is a high-performing, heavy-duty detergent. It is formulated with special surfactants and alkaline cleaners that have been developed into a foaming, no-rinse product. Evap Foam is ideal for use on most coils, but it is particularly suited for use on cooling or evaporator coils. The aerosol can be sprayed either right side up or upside down. NSF registered. Can be used with the Talon Flexible Aerosol Wand (4776-0) for hard to reach locations.

18 ounce can	4171-75



Cal-Blast®

Cal-Blast is a no-rinse condenser cleaner that will powerfully separate undesirable materials from the surface, offering maximum cleaning of finned coils. It's a high-performance aerosol with excellent solvency and blasting spray.

20 ounce can	4132-20

Not available for sale in California



Nu-Blast®

A no-rinse condenser coil cleaner in a convenient aerosol package. Double action of high-pressure blast and solvent cleaning restores design efficiency of condenser coils. It is non-flammable and nonconductive. No rinse required — cleaning solvent evaporates completely. Use with adequate ventilation.

8 ounce	can	4290-75
o ounce	Can	4290-73

Not available for sale in California



Evap-Fresh® No Rinse†

Evap-Fresh is a ready-to-use, no-rinse cleaner and disinfectant for evaporator coils. It effectively cleans, as well as controls, mold and bacteria. This onestep no-rinse disinfectant cleaner is perfect for air conditioners, commercial air handling units, HVAC cooling coils, refrigeration equipment, and evaporator coils. EPA registered specifically for use on HVAC equipment. Can be used with the Talon Flexible Aerosol Wand (4776-0) for hard to reach locations.

18 ounce can	4166-75
--------------	---------



Talon

Talon is a flexible aerosol wand for Nu-Calgon's Evap Foam No Rinse, Blackhawk, Evap-Fresh No Rinse or PenetrateHD products. Provides focused cleaner spray or penetrant in tough-to-reach locations. The Talon is highly flexible, retains shape memory, and provides 27 inches of added length to an aerosol canister for navigating in tight quarters inside the equipment. The reusable Talon is a must-have service tool!

1 each	4776-0
--------	--------

+ Product not registered for sale in Canada.

A/C Shine®

Superior Cleaner/Protectant

A/C Shine is specially formulated to clean and protect the painted metal surfaces of outdoor A/C condensing units. It sprays on and wipes off quickly and easily without water. For use on all outdoor unit painted surfaces.

	Nu-Calgon	ClenAir
12 oz.	61118	ACS12

DuraCoil

DuraCoil is a long-lasting coating for coils and surfaces in corrosive environments. It uses a durable, OEM-approved Heresite® coating. DuraCoil has a fast, air-dry formula that bonds to all metals and causes negligible heat transfer loss across the coil. Great for repairing an OEMapplied coil coating that has been compromised while in service! Brown in color.

11 ounce can 4083-90



CleanVu Glass Cleaner

CleanVu is a highly effective aerosol cleaner for glass and all hard, non-porous surfaces. Its fast-drying, non-filming formula cleans dirt and grime, providing streak-free shine.

Stainless Steel Cleaner

Nu-Calgon's aerosol Stainless Steel Cleaner removes light soil and restores shine to stainless steel, chrome and hard, washable surfaces.

CleanVu 19 ounce can	4081-85
Stainless Steel 15 ounce can	4084-75



Pipe-Dri®

Pipe-Dri aerosol insulation provides a moisture barrier to stop sweating and dripping on refrigeration lines, air conditioning lines, and other cold surfaces. Quickly adheres and dries to a hard waterproof coating. Pipe-Dri makes it possible to insulate hard-to-reach areas.

4297-75 18 ounce can

Not available for sale in California



Zinc Rich Cold Galvanizing

Zinc Rich is highly resistant to nearly all forms of corrosion. Perfect for repairing factory galvanized material damaged in shipment, welding, assembly, etc. Its 95% pure zinc film fuses itself to iron, steel, or aluminum. Blends well with hot-dip coating. Meets or exceeds military specifications MIL-P- 26915A, MIL-T- 26433, MIL-P- 21035, MIL-P-46105 and the Preece Test.

13 ounce can	4087-03



Pump Protector

Protects seasonally operated pumps against corrosion during shutdowns by "winterizing" them. When corrosion occurs in close-tolerance areas, it can cause the impeller to stick or bind. It is safe for all types of water pumps and requires no special rinsing at start-up.

4299-T8 10 ounce can



Degreasing Solvent EF

A degreasing solvent, specially formulated for cleaning and degreasing equipment where washing or flushing is not possible. Simply spray on and wipe off. Penetrates guick and deep, loosening and liquefying heavy greases and tar. Non-corrosive and non-staining with a dielectric strength over 26,000 volts.

14 ounce can	4083-75
14 ounce can - LV*	4083-83

* LV = Low VOC for California Utah and New Hampshire

Aerosol Specialty Products



Pan-Spray®

Pan-Spray is an effective, easy-to-use waterproof rubberized coating that won't chip, flake, or peel. It's ideal for sealing out rust and corrosion as well as repairing leaky condensate pans, cooling towers, swamp coolers, roofing, gutters, and down spouts. Pan Spray is the perfect solution for emergency and permanent repair.

16 ounce can - White	4296-50
16 ounce can - Black	4296-51



Nu-Kill® Max Strike Wasp and Hornet Killer[†]

A "quick-kill" spray formulation EPA registered to instantly and effectively kill wasps, hornets, yellow jackets and scorpions, from distances up to 20 feet. Nu-Kill also kills with residual action as wasps and hornets return to a treated nest. The formula is safe in and around electrical equipment, having a dielectric strength of 57,200 volts.

1		
1	13.5 ounce can	4292-75



Clen Air.

PenetrateHD® Super Penetrating Lubricant

PenetrateHD loosens rusted and frozen metal parts. Frees stuck fan blades, blower shafts, pulleys, rusted nuts and bolts, and any frozen, rusted, or seized metal part. Unique low surface tension formula penetrates into the smallest spaces and breaks and dissolves the bonds of rust and corrosion. Lubricates, protects metals and displaces water. Dielectric strength 40,000 volts. Can be used with the Talon Flexible Aerosol Wand (4776-0) for hard to reach locations.

12 ounce can	61105
17 ounce can	61106
12 ounce can - LV*	61107
17 ounce can - LV*	61108

* LV = Low VOC for California



Electrical Contact Cleaner

Cleans and protects electrical contacts from corrosion. Safe on most plastics. Quickly removes greases, dust, and oxidation, restoring and maintaining precision and efficiency to the instrument and component. Includes extension tube for accuracy. Dielectric strength over 25,000 volts. USDA approved.

11 ounce can	4082-03
14 once can - LV *	4082-04

* LV = Low VOC for California and Canada



Food-Grade Silicone

Food-Grade Silicone sprays a perfect non-stick surface on ice machine surfaces, vending machines, coin slots, slicing machines, dairy machinery, and other food processing and packaging equipment. An excellent lubricant that prevents binding and sticking. Contains ingredients approved by the FDA for food contact use. USDA approved.

11 ounce can	4084-03
--------------	---------



V-Belt Dressing

V-Belt Dressing is specially formulated to penetrate and extend modern V-Belt life. It is particularly effective in maintaining V-Belt efficiency and performance under today's increasing performance requirements. It keeps belts pliable, prevents slippage, and does away with squealing and chattering. Also good for leather, rubber, canvas and other fabric belts, flat or round. USDA approved.

11 ounce can	4086-03
--------------	---------

Aerosol Adhesives



Spray-n-Bond™

Spray-n-Bond is a wide web spray adhesive formulated specifically for insulation and duct liner applications. Ideal for porous surfaces, it is waterproof, flexible, transparent, and nonstaining. Formulated with the environment in mind, it contains no chlorinated solvents or ozone depleters. Will work with cardboard, most plastics and cloth. Cleans easily with degreasing solvent.

12	ounce can	4369-75
12	ounce can-LV*	4369-85

* IV = I ow VOC for California



Spray Adhesive

Spray Adhesive is a fast-drying, all-purpose product that provides a strong, water-resistant, flexible bond. It is translucent and does not penetrate or soak material causing bleedthrough. Spray Adhesive is excellent for labeling, bonding, splicing and sealing paper, cardboard, cloth, rubber, styrofoam, canvas, leather, wood, and most plastics.

12 ounce can	4080-04
--------------	---------

† Product not registered for sale in Canada.

PRODUCTS

AEROSOL



Great Wipes

Great Wipes Industrial Strength Hand Towels are waterless wipes made specifically for the air conditioning, refrigeration, and plumbing service technician. Each premoistened, heavy duty towel has strong pumice scrubbing power that conveniently cleans anywhere and anytime.

75 count canister	4185-75	(NSF)



Scrubs-In-A-Bucket® HVAC80

The original Scrubs — disposable, pumice-performance waterless hand cleaner towels that effectively and quickly clean hands on a wide variety of industrial soils and greases. Each self-dispensing portable canister contains perforated disposable heavy-duty towels and are pre-moistened with the famous Scrubs cleaning formulation. Effective yet gentle to the skin. Use anywhere, anyplace, anytime.

30 count canister	4366-24	(NSF)
80 count canister	4366-87	NOL



Quick Seal™ Pipe Repair

A permanent knitted fiberglass impregnated tape that is designed for quick, in-the-field repair of leaks for all types of pipes. It can be used on both cold or hot water, as well as refrigeration, plumbing, industrial, commercial, and residential applications. It is safe for potable water and is UL listed. ANSI/NSF Standard 61.

2" x 4' wrap	4299-10
4" x 12' wrap	4299-11



Pneu-flush®

A flushing and cleaning system specifically designed for pneumatic control air lines. It utilizes DuPont® Vertrel® XM, a premier ozone-safe HFC cleaning solvent. Pneu-Flush works quickly and easily to clean and purge the compressed air lines in HVAC control and other pneumatic systems.

2 lb. canister	4298-01
Injection Valve	4300-89

(Injection Valve fits R_X11-flush® and Pressurized Rx-Acid Scavenger® as well)



Thermo-Trap® Paste

Thermo-Trap is the industry's original heat absorbing paste designed to isolate heat encountered in soldering, welding, and brazing, thereby preventing damage to nearby heat sensitive controls or fittings. USDA approved. Biodegradable.

11 ounce tube	4371-36



Thermo-Trap® Gel

Thermo-Trap Spray gel is designed to form a protective barrier to keep flames and heat from damaging areas beyond direct work surfaces during brazing or soldering. It will protect drywall, wiring, joists, and surrounding areas that a flame could also come in contact with. Cleans up easily with no residue.

1 quart spray bottle	4371-32	
4 fluid ounce spray bottle	4371-53	





Green Clear

Green Clean is a pleasantly scented, all-purpose, environmentally friendly cleaner designed for the rapid removal of grease and other heavy soils on coils and other surfaces. It can be used right out of the bottle or diluted for milder jobs. Biodegradable. Also great for microchannel coils.

1 quart spray bottle	4186-24
1 gallon bottle	4186-08
55 gallon drum	4186-01



Grez-Off® Heavy Duty Degreaser

Grez-Off works hard so you don't have to. This heavy-duty answer to heavy-duty grease and grime leaves engines, machinery, asphalt, garage floors and more whistle clean. Biodegradable, non-flammable formula hits hard and fast with less impact on user and environment.

	Nu-Calgon Number	Clen Air Number
1 gallon	61116	22701
32 oz. spray	61117	23732



Spray Nine® Cleaner & Disinfectant

Spray Nine is a tough task cleaner and broad spectrum disinfectant. EPA-registered disinfectant kills harmful germs like HIV-1, Influenza, H1N1, Staphylococcus Aureus, Salmonella Choleraesuis and E. Coli in 45 seconds. Also helps prevent cross contamination. Authorized by USDA for use in federally inspected meat and poultry plants with a C-1 rating.

	Nu-Calgon Number	Clen Air Number
1 gallon	61110	26801
32 oz. spray	61113	26832

Other Specialty Products



Elite® Performance Windshield Washer Fluid -20°

Elite Performance Windshield Washer fluid is independently tested to provide freeze protection to -20°F. Don't take chances with generic washer products; only Elite Performance offers certified protection.

	Nu-Calgon Number	ClenAir Number
1 gallon	61115	CAWW1G



ClenHands: Orange Smoothie™, Orange Crush™ and Cherry Crush™

Premium antimicrobial hand cleaners that quickly dissolve dirt, grease, fuel oil, pipe dope, resin, ink, paint, glue, rubber gasket and tile cements, and many other hard-to-remove soils. ClenHands Orange Smoothie is a smooth non-pumice formula. ClenHands Orange Crush is enhanced with fine-ground American pumice. ClenHands Cherry Crush is a cherry-scented antimicrobial hand cleaner with pumice. For use with or without water.

			Nu-Calgon Number	ClenAir Number
П	Orange Crush with Pumice	1 gallon	61201	2201
	Orange Crush with Pumice	15 oz.	61203	2215
	Orange Smoothie Non Pumice	15 oz.	61202	2202
	Cherry Crush with Pumice	15 oz.	61204	2315
1	ClenHands Super Gel	11 oz.	61205	2414



Smoke Pens

Smoke Pens are excellent for observing ventilation, air balancing, smoke detectors, drafts, leakage, and air flow. Smoke tests will effectively and inexpensively reveal leaks in heating and air conditioning duct work, furnaces, fire boxes, exhaust fans, and smoke detectors.

	Nu-Calgon Number	ClenAir Number
Smoke Pen with 6 wicks	61305	CASP1
Refill Package - 6 wicks	61306	CASP1RW

SPECIALTY PRODUCTS

Perma-Wrap™ Foam Insulation Tape

Perma-Wrap is formulated from the highest quality elastomeric thermal insulation material. Its closed cell construction seals out air and moisture, slowing down heat transfer, and can be used on hot or cold water pipes, chilled water, and refrigerant lines to prevent sweating and condensation. Service temps as low as -40°F with a high continuous temperature of 160°F and a high intermittent temperature of 220°F.

2" x 1/8" x 30' roll	4218-W3
2" x 1/8" x 30' roll - dispenser package	4218-12



Cork Tape

Cork Tape is formulated and manufactured as an insulating material for preventing sweating and condensation on refrigerant lines, cold pipes, and other commercial refrigeration and A/C systems. Serves as an excellent insulator on hot pipes, and can also be used as a gasketing material, a sound-deadening material, and for wrapping valves, tees, and fittings. Service at temps as low as -30°F, as high as 200°F and won't sag up to 350°F.

2" v	1/8" x 30	roll	1217	ハハつ



Foam-Tite®

Foam-Tite is an economically priced tape formulated from quality thermal insulation material. With closed cell construction, it can be used on cold water pipes and chilled water and refrigerant lines to prevent sweating and condensation. Can also be used on hot water lines for better insulation against heat loss. Service temperatures of -15°F to 160°F.

<u>"</u>	х	1/8	8" x	30'	roll	4219	-1



Cork-Tite®

Cork-Tite is an economically priced tape used to insulate cold pipes and stop condensation problems. Ideal for preventing heat loss in hot pipes, and used as an effective sound dampening material. Also sticks to dry metals and seals tightly without drying, while staying flexible within the service temperatures of -5°F to 200°F.

2" x 1/8" x 30' roll 42'



Foam Tape PE

Foam-Tape PE is an insulation tape with closed cell construction, providing an economical way to prevent sweating or condensation on air conditioning, refrigeration, chilled water, or other cold lines. Also used on hot water lines for insulation against heat loss, with service temperatures of -70°F to 175°F.

)" v	1/8"	v 30′	roll	421	9-20
4 X	1/0	スコリ	IUII	44	フームリ



Thumb-Tite®

Thumb-Tite is formulated and manufactured for use in many sealing, insulating, and general indoor/outdoor maintenance applications. Excellent adhesion capability and is non-staining, non-hardening, and unaffected by wide variations in temperature - an excellent thumbing grade. Each box contains two 1-pound bars. Service temperatures of -20°F to 350°F.

2 lb. box	4216-92
Z 10. DUA	72 10-22



Nu-Foam®

Nu-Foam is double expansion polyurethane foam with all-direction dispersing. Used as a sealant and insulating product on openings created for refrigeration, air conditioning and heating tubes or pipes, duct joints, and other areas where unwanted air penetration might occur. Contains no CFCs or HCFCs, and is fire retardant and UL listed.

12 ounce can	4293-04
20 ounce can	4293-75



Sealing and Caulking Cords

Sealing and Caulking Cords are nonstaining sealers formulated to be water-resistant, dust-resistant, and white in color. They securely adhere to most surfaces and provide excellent insulation value. They are available in 3/8" pre-shaped extruded cords, with serrated release paper. Used indoors and outdoors, it stays flexible at -20°F and non-sagging at 350°F.

3/8" x 25' roll	4216-27
-----------------	---------

Propylene Glycol



Freez-Kontr'l®

Freez-Kontr'l is an expanded family of heat transfer fluids (anti-freeze) based upon non-toxic propylene glycol. All products are fully formulated to provide optimum freeze protection, as well as corrosion protection in chilled water, hydronic, and other closed systems. Safe to use where contact with potable water is possible. GRAS certified.

- Freez-Kontr'l provides greater than -60°F freeze protection and greater than -100°F burst protection.
- Freez-Kontr'l 95/5 a fully concentrated (~100%), inhibited propylene glycol product.
- Freez-Kontr'l 35 formulated with 35% propylene glycol for use as a secondary coolant in supermarket rack applications.
- Freez-Kontr'l FG a certified USP, food grade propylene glycol product at ~100% concentration. Inhibited. NSF registered.

1 gallon bottle	4188-07	
5 gallon pail	4188-05	
55 gallon drum	4188-02	
5 gallon pail	4188-06	
55 gallon drum	4188-03	
55 gallon drum	4188-35	
55 gallon drum	4188-04	NSF)
	5 gallon pail 55 gallon drum	5 gallon pail 4188-05 55 gallon drum 4188-02 5 gallon pail 4188-06 55 gallon drum 4188-03 55 gallon drum 4188-35



Burst-Kontr'l® AP-100

Burst-Kontr'l is a specially formulated propylene glycol heat transfer solution for use in boilers having aluminum heat exchangers. It has corrosion inhibitors to protect aluminum, copper, solder, brass, and steel. Provides burst protection to -100°F and freeze protection to -60°F.

5 gallon pail	4187-15

Ethylene Glycol



Freez-Therm®

Freez-Therm is an inhibited heat transfer fluid and anti-freeze based upon ethylene glycol. It can be used in chilled water, hydronic, and other closed systems for both freeze point suppression and corrosion inhibition. An uninhibited version is also available in drums on special order.

1 gallon bottle	4189-07
5 gallon pail	4189-05
55 gallon drum	4189-01

Glycol Tools and Equipment



Glycol Refractometer

An accurate and economical tool for ensuring proper levels of glycol treatment in HVAC fluid systems. Removes guess work and prevents wasteful over-treatment. It has metal body with cushioned eyepiece, focus adjustment, and a rubber hand grip. A calibration screwdriver, calibration fluid, a plastic pipette, optical cleaning cloth, and a rugged carrying case are included.

	Nu-Calgon Number	ClenAir Number
1 each	61301	GLY32



Glycol/ Oil Transfer Pump

Heavy-duty pump designed to transfer Freez-Kontr'l®, Freez-Therm®, or oil products (up to 1000 sus) from Nu-Calgon supplied 55 gallon drums to their application.

1017	1 each	4817-0
------	--------	--------

GLYCOLS

WATER TREATMENT



Ty-lon® B20

Ty-lon B20 is a liquid nitrite-borax corrosion inhibitor and dispersant for closed recirculating systems. It combines corrosion inhibitors, a unique copolymer dispersant, and a color indicator to facilitate leak detection, into a complete treatment for hot and chilled water closed systems containing ferrous and non-ferrous metal components.

gallon pail	7537-05



Ty-lon® B14A

Ty-lon B14A is an all-in-one boiler treatment product that controls scale, corrosion, and condensate line corrosion in low pressure, low make-up steam heating boilers where 90% or more of the condensate is returned. It is chromate-free and contains a color indicator for visual determination of treatment residual. Its balanced formulation provides an energy-efficient way of heating.

5 gallon pail	7519-05
---------------	---------



System Cleaner

System Cleaner is a liquid, heavy-duty industrial alkaline cleaner specifically formulated to emulsify and clean equipment surfaces and pipe fouled by cutting oils, grease, lubricants, corrosion products, and other debris.

C wallaw wait	4270.00
5 gallon pail	4370-08

Water Test Kits

Bacteria Test Kit

Kit contains 10 agar paddle tests that are used to monitor bacterial contamination in cooling tower and evaporative condenser water. Test can be performed in a lab or on site. Each side of the paddle is coated with TTC Agar, material that supports growth of most common bacteria. Regular testing will detect and show when bacteria counts are rising.

Bromine/Chlorine Test Kit

Kit measures free and combined halogen (chlorine, bromine), and it should be used to support treatment with Bromicide Tablets. Residual can be expressed as 0.2 ppm or 0.5 ppm of free halogens. Dropper technique is used.

1 each	4803-0
--------	--------

Complete Test Kit

The complete test kit for cooling water and boiler water application testing. In addition to pH, this kit also provides tests for obtaining alkalinity, nitrite, hardness, sulfite, and chloride levels.

1 each	W017-0
--------	--------

No. 89A Test Kit

No. 89A Test Kit contains tests for determining hardness, pH, chloride and alkalinity, as well as treatment residual tests for Ty-lon C70, Cal-Treat 233, No. 340 Liquid Scale Inhibitor, and Ty-lon B20.

1 each	4798-2
i each	4/98-2

Nitrite Test Kit

Used for testing treatment residual of Ty-lon B20 and Ty-lon B14A. It is a cerric ammonium nitrate (can) titration method, and it can be used in systems containing glycol. Each drop equals 40 ppm of nitrite.

1 e	ach	4797-0

Organic Phosphonate Test Kit

Used to determine the treatment residual of No. 340 Liquid Scale Inhibitor, Ty-Ion C70, and Cal-Treat 233.

1 each	4804-0
--------	--------

Scale Removal



Working Strength



pH Color Indicator

Neutralized

Nu-Calgon's exclusive "built-in" pH color indicator tells you when to add more acid, and it lets you see when the system is clean. At working strength, the acid cleaning solution is green or light blue. When the acid solution is neutralized and is no longer working, the solution turns purple and more acid must then be added. The system is clean when the green color is retained for 20-45 minutes.

Competitive Product with Dangerous Foam Nu-Calgon Low-Foaming Liquid Scale Dissolver



Low-Foaming Performance

To demonstrate its greater low-foam property, Liquid Scale Dissolver was added to a beaker containing lime scale. A leading competitive liquid product was added to another beaker containing an equal amount of lime scale. See the difference! When cleaning towers and evaporator condensers, low-foam is the preferred approach as high foam is dangerous to both personnel and surroundings.

Liquid Scale Dissolver

Liquid Scale Dissolver is a hydrochloric (muriatic) acid formulated to remove calcium scales from cooling towers and other water-cooled equipment. It contains low-foaming corrosion inhibitors and a built-in pH color indicator to let you know when the acid has been neutralized. pH test paper is also included. USDA approved.

1 gallon bottle	4330-08
5 gallon pail	4330-05
55 gallon drum	4330-01



Eco-Lyme®

Eco-Lyme is a new chemistry for the HVACR market that provides a unique blend of performance with a desired eco-profile. The product is specially formulated to achieve descaling behavior of competing hydrochloric acid-based chemistry descalers. However, the active ingredient is substantially safer on equipment metals. Eco-Lyme is ideal for stainless steel construction to eliminate potential issues of localized corrosion/pitting caused by repeated use of hydrochloric acid. Eco-Lyme is odorless, making it safer to use in the field. NSF registered.

1 gallon bottle	4167-08	
5 gallon pail	4167-05	(NSF)
55 gallon drum	4167-01	



Season Start® "Imperial Grade" Scale Remover

Season Start is a powdered sulfamic acid formulation that contains the best inhibitors available for protecting all metals, including galvanized metal. It is the best and the safest dry acid cleaner available. It contains a built-in pH color indicator to let you know when the acid solution has been neutralized, as well as wetting and anti-foaming agents. USDA approved.

10 lb. container	4360-88
50 lb. pail	4360-84

Initial Dosage Recommendation			
Tons of Horsepower	Liquid Scale Dissolver	Eco-Lyme	Season Start
10	2 gallons	4 gallons	10 lbs.
30	5 gallons	10 gallons	30 lbs.
50	10 gallons	20 gallons	50 lbs.
90	15 gallons	30 gallons	75 lbs.



Vital-Flo® Tankless Water Heater Descaler Kit

The Vital-Flo Tankless Water Heater Descaler Kit is a complete service tool for descaling tankless water heaters. It consists of a submersible descaler pump, a set of 5-foot long hoses with 3/4" female hose threaded assemblies, formulated descaler solution packaged in a lidded 4 gallon chemical resistant container. The solution is also available separately. NSF registered.

Vital-Flo kit	4387-01	NSE
Vital-Flo descaler solution	4387-02	NOL



Season Treat

Season Treat utilizes 6Rsp Micromet, a slowly dissolving phosphate, contained in a unique flow-through package. The package design makes it simple to treat small cooling towers and evaporative condensers. Simply unwrap the package and place it in the sump. One canister treats up to 10 tons for scale (5 tons for corrosion) for five to six months.

1 canister 4364-88	1 canister
--------------------	------------



Ty-lon[®] C70

Ty-lon C70 is an all-organic liquid scale, deposit, and corrosion inhibitor for use in open recirculating cooling water systems, evaporative condensers, and air washer systems. This treatment program is particularly effective in preventing scale deposits in systems that utilize make-up water with high scaling potentials.

5 gallon pail	7597-05
15 gallon pail	7597-P3
55 gallon drum	7597-01



No. 340 Liquid Scale Inhibitor

No. 340 is an extremely concentrated scale inhibitor that is effective in hard, highly alkaline water. It is very stable and does not form any sludge. It is most effective at treatment levels between 10 and 15 parts per million. A constant, accurate feed is accomplished with a Drip Feeder or CMS Feed Pump. USDA approved.

1 gallon bottle	4340-08
5 gallon pail	4340-05
55 gallon drum	4340-01

Feeding Equipment



No. 31-TX1 Acid Pump

Compact submersible pump designed for circulating strong acids and cleaning solutions. All parts are constructed of acid-resistant materials.

1 each 46	603-0
-----------	-------



HK-31 Hose Kit

An accessory item available for use with the No. 31-TX Acid Pump. Kit includes two 1/2 inch tubing adapters, two 10 foot sections of 1/2 inch clear plastic tubing and three hose clamps.

1 each 4604-0		
	l each	4604-0

To Inhibit Scale Formation				
Tons of Refrigeration or Horsepower	Containers of Season Treat	Ty-lon C70 Required per Month	No. 340 Liquid Scale Inhibitor Required per Month	Bleed-off for Most Scale-forming Waters
10	1	1/4 gallon	1/4 gallon	1/8 gpm
30	3	2/3 gallon	1/2 gallon	1/3 gpm
50	5	1 gallon	3/4 gallon	1/2 gpm
100		2 gallons	1 1/2 gallons	1 gpm
120		2 1/2 gallons	2 gallons	1 1/4 gpm
150		3 gallons	2 1/2 gallons	1 1/2 gpm

Corrosion Prevention



Cal-Treat® No. 233

Cal-Treat No. 233 is a liquid formulation that is used for controlling severe corrosion in evaporative condensers and cooling tower systems. It is based upon a synergistic formulation of zinc, molybdate, and organic phosphonate. Provides superior corrosion control and inhibits scale accumulation.

5 gallon pail 4149	-05
--------------------	-----

To Control Corrosion		
Cal-Treat No. 233 Required per Month	Bleed-off for Most Corrosive Waters	Capacity of System in Tons of Horsepower
1/3 gallon	1/10 gpm	10
1 gallon	1/4 gpm	30
2 gallons	3/8 gpm	50
3 gallons	1/2 gpm	90

Algae Prevention



No. 85 Algaecide[†]

No. 85 Algaecide is a polymeric, cationic biocide that has been developed for controlling biological growth in equipment. It is an EPA registered product to kill algae, bacteria, and fungi in recirculating water systems, industrial air washing systems, and closed systems.

1 gallon bottle 4108-08



Bromicide Tablets[†]

A chlorine-bromine donating organic compound in tablet form. It slowly releases powerful oxidizing hypohalous acids, which prevent algae and slime bacteria fouling in open recirculating cooling water systems and evaporative coolers. It also has the capability of breaking up and removing existing biological mass from system surfaces. USDA approved and EPA registered.

50 lb. pail	4109-M9
50 lp. pali	4109-1419

To Kill Algae or Slime Growth			
Tons of Refrigeration or Horsepower	Gallons of No. 85 Algaecide per Month	Number of No. 90 Bromicide Tablets for an Average System	
10	1/6 gallon	5	
30	1/3 gallon	15	
50	1/2 gallon	25	
90	2/3 gallon	45	

Other Water Treatment Products



Humidi-Pro™

Humidi-Pro is designed for humidifiers using up to 25 gallons per day and will inhibit scale for one season. Install Humidi-Pro on the water line that supplies water directly to the humidifier.

1 each	4190-02
--------	---------



pH-Treat™

pH-Treat is an in-line treatment product specifically for the treatment of the acidic nature of the condensate water produced by today's high efficiency furnaces. Includes fitting kit for easy installation.

installation.		
1 each	4720-06	

†Product not registered for sale in Canada.

WATER TREATMENT



Evap-Treat®

Evap-Treat is used in evaporative coolers or "swamp coolers" to prevent scale and corrosion. Place it in the cooler sump and it will last all season long, thereby increasing pad life. Utilizes 6R Micromet®, a slow dissolving polyphosphate.

1 each (coolers up to 6,500 cfm)	4173-04
1 each (coolers up to 10,000 cfm)	4173-06



Water Sample Bottles

The proper way to treat a cooling tower, closed loop system, or ice machine is to have the supply or makeup water tested. Nu-Calgon provides this valuable service for free and will analyze the water and recommend effective treatment. These bottles can also be used to send in glycol samples to test freeze points.

1 each (3 bottles)	4995-0



No. 215 and No. 1075 Drip Feeders

Used for feeding No. 340 Liquid Scale Inhibitor, Cal-Treat 233, Ty-Ion C70 and No. 85 Algaecide. Calibrated at the factory to ensure accurate feeding. Provides the benefits of continuous treatment for small systems without the high cost usually associated with automatic feeding equipment.

No. 215 Drip Feeder	4669-W3
No. 1075 Drip Feeder	4670-W3



Jug Holders

These should be used when drip feeding any of Nu-Calgon's liquid water treatment products. Once secured to the cooling tower or evaporative condenser, they will hold the 1 or 5 gallon containers in the proper position.

1 gallon holder	4606-0
i ganon noidei	1000 0



No. 20L and No. 100L Feeders

Steel tanks suitable for pressures up to 150 psi and temperatures up to 212°F. Uses 3/4 inch FNPT connections for installing on bypass to any size line. Use No. 20L Feeder for initial charges up to 20 pounds (or 2 gallons). Use No. 100L Feeder for initial charges up to 100 pounds (or 10 gallons). Inlet/outlet strainers not included.

No. 20L Feeder	4628-0
No. 100L Feeder	4650-0

Plumbing Products



Drain Solve

Ideal for condensate pan drains, Drain Solve saves time and money with its ease of use. It eliminates application concerns associated with more reactive, fuming drain openers. Simply pour it down the drain and let it work without fear of noxious fumes or reactions. Does not contain sulfuric acid.

1 quart	4165-24	NSF
1 gallon	4165-08	NOL



Calci-Solve

Remove scale from lines and clear clogged drains easily and effectively with Calci-Solve. The product includes a special inhibitor that coats the inside of the pipes with a protective film, allowing the acid in Calci-Solve to quickly dissolve calcium, magnesium, sodium, lime, rust, and other elements without harming pipes.

1 quart	4134-24
1 gallon	4134-08



UrinaKleen

Keep urinals free flowing with UrinaKleen. Use it to dissolve urinary salts, mineral scale, and rust deposits which are found in urinals. It also attacks the primary source of odors.

1 quart	4590-24
1 gallon	4590-08



A/C Drain Sucker®

A/C condensate drain pan overflow is caused by slime and sludge that builds up and clogs the drain line. The A/C Drain Sucker quickly removes the clog and the excess water, resolving the overflow problem. The kit includes a PurCool® Green 3 ton tablet to provide months of preventive treatment and free flowing drains, as well as all fittings and hoses for suction or pressure applications.

	Nu-Calgon Number	ClenAir Number
A/C Drain Sucker kit	61308	CADS1
PurCool Green 3 tons tablet	61048	



Vital-Flo® Tankless Water Heater Descaler Kit

The Vital-Flo Tankless Water Heater Descaler Kit is a complete service tool for descaling tankless water heaters. It consists of a submersible descaler pump, a set of 5-foot long hoses with 3/4" female hose threaded assemblies, and a formulated descaler solution packaged in a lidded four gallon chemical resistant container. The solution is also available separately. NSF registered.

Vital-Flo kit	4387-01	NSE
Vital-Flo descaler solution	4387-02	NOE

WATER TREATMENT



iWave®-M Mini-Flexible Air Purifier for Ice Machines

Versatile ion needles mounted in a flexible bar circuit

- For HVAC cooling coils up to 36" wide
- Kills mold and mildew—keeps coil cleaner
- For ductless systems (mini-split, PTAC) and ice machines
- Chemical and temperature resistant, durable for long service life
- Voltage input 110VAC to 240VAC

each	4900-35
cucii	1,700 33



Nickel-Safe Ice Machine Cleaner

The original Nickel-Safe Ice Machine Cleaner. It is a food-grade citric-phosphoric acid product for removing scale deposits from ice machines having nickel-plated or tin-plated evaporators, and it is acceptable for use in all ice machines containing nickel. It mixes to form a green solution, which makes rinsing easier. USDA approved.

16 fluid ounce bottle	4287-34
1 gallon bottle	4287-08



Liquid Ice Machine Cleaner

Liquid Ice Machine Cleaner is a food-grade phosphoric acid that is fast acting, yet safe to use. It has been formulated to remove scale deposits from ice machines and coffee urns. It does not give off any harsh fumes or contain chlorine or chlorides that would attack stainless steel. USDA approved. NSF registered.

8 fluid ounce bottle	4207-47	NSE
1 gallon bottle	4207-08	Mar



IMS-III Sanitizing Concentrate[†]

IMS-III is an EPA registered sanitizing concentrate formulated to sanitize hard, non-porous surfaces and to eliminate odors and slime growths. No rinsing is required when diluted to 1.6 ounces per gallon. Formulated for general use in ice machines, ice cream dispensing equipment, and other food processing equipment.

16 fluid ounce bottle	4211-34
-----------------------	---------



6Rsp Micromet®

6Rsp Micromet is a slow dissolving phosphate specifically formulated for inhibiting scale in ice machines and other equipment using low volumes of water. It is used in Nu-Calgon scale controlling cartridges and requires replacement once every six months. Typical dosage is 8 ounces per 500 pounds of ice (50 gallons of water) a day.

50 lb. pail	4265-50	(NSF)

+ Product not registered for sale in Canada









Heads











QL3B Single System Head

Used with any Everpure filters. Head includes a water shut-off valve with mounting bracket and screws. (3/8" NPT)

1 each	4621-07
I Eacii	1 1 02 1 - 07

QC7I Single Head

Ideal for all Everpure filters. Head includes a shut off valve, flushing valve, and outlet pressure gauge on a box bracket design. (3/8″ NPT)

QC7I Twin Parallel Head

Dual filter head that is parallel plumbed for two Everpure filters, either mix or match. Head includes a shut off valve, flushing valve, and outlet pressure gauge on a box bracket design. (3/4" NPT)

1 each	9272-22 (4621-02)

QC7I Triple Parallel Head

Triple filter head parallel plumbed for three Everpure filters. Head includes a shut off, flushing valve, and outlet pressure gauge on a box bracket design. (3/4" NPT)

1 each 92	72-23 (4621-03)
-----------	-----------------

QC7I Quad Parallel Head

Quad filter head parallel plumbed for four Everpure filters. Head includes a shut off valve, flushing valve, and outlet pressure gauge on a box bracket design. (3/4" NPT)

1 each	9336-11 (4621-04)
--------	-------------------

*Everpure® is a trademark of Everpure, Inc., Westmont, IL.

EVERPURE® WATER FILTRATION



Kleensteam CT and Kleensteam II

Everpure's second generation water treatment system for steam applications.

Kleensteam is a total system delivering high quality filtered water with scale inhibition, as well as deliming capabilities. The dual cartridge design provides enhanced performance for low and high flow capacity steamers and flexibility for expanding to meet future needs. Kleensteam also reduces chlorine-induced corrosion. It's simple to install, operate, and

Kleensteam CT	1.67 gpm max. flow	9797-50
Kleensteam II Single	2.5 gpm max. flow	9797-21
Kleensteam II Twin	5.0 gpm max. flow	9797-22



High Flow CSR Manifold with Prefilter

Utilizing the nu-MC² or the nu-XC² cartridges, this system provides premium quality water to high flow fountain dispensers, coffee makers, and ice machines. New and improved Micro-Pure II media inhibits the growth of bacteria. High Flow CSR reduces chlorine taste and odor and other offensive contaminants that can adversely effect the taste of beverages. Precoat submicron technology reduces dirt and particles as small as 1/2 micron and reduces health contaminants such as cysts. Additionally, the SRX Housing inhibits scale when it is equipped with scale-inhibiting IMF-10 ScaleSticks®.

High Flow CSR Manifold with Prefilter					
Twin Triple Quad					
10″	9294-02	9294-03	9294-04		
20″	9294-22	9294-23	9294-24		



Coldrink/Insurice Systems

The Coldrink/Insurice manifolds can be used with any Everpure cartridges. i.e. the MC² or XC² for carbonated beverages or i2000² or i4000² for ice machines. Utilizes the systems' existing 10" or 20" prefilter on a single, twin, triple, or quad manifold. Systems come with the initial EC110 or EC210 prefilter cartidge. Just purchase the appropriate Everpure cartridge for your application.

Coldrink/Insurice Manifold with Prefilter				
Single Twin Triple Quad				
10″	9293-01	9293-02	9293-03	9293-04
20″	9293-21	9293-22	9293-23	9293-24

Cartridges



4SI and 7SI Cartridges

Specially designed for ice machines. This cartridge does not include carbon, which allows for compliance with ASHRAE Standard 188. The cartridge reduces sediment and particulate down to 1/2 micron and reduces cyst and Giardia. The filter allows chlorine to pass through, which helps reduce slime and bacteria growth inside the ice machine and ice bin. Helps reduce water borne bacteria that can cause Legionnaires' Disease. Ideal for food service operations where baking of bread and pastries is done on-site.

- Scale inhibition
- Cyst reduction
- NSF standards 42

- Particulate reduction
- 1/2 micron rating

Capacity: 15,000 gallons • 2.0 gpm flow rate

(NSF) 9606-01

9606-51

Capacity: 25,000 gallons • 3.5 gpm flow rate

Visit us at www.nucalgon.com or call 1-800-554-5499

Cartridges



i2000² and i4000² Cartridges

Reduces water-related ice machine problems caused by scale buildup from dirt and dissolved minerals. Provides superior taste and odor reduction of chlorine and other offensive contaminents with filtration of particles as small as 1/2 micron.

- · NSF certified under NSF/ANSI standards 42 as well as 53, which reduces parasitic protozoan cysts, such as Cryptosporidium and Giardia
- Micro-Pure® II media limits the passage or growth of bacteria that may already exist in the incoming water

i2000²	9612-27 (4621-10)	(NSF.)
Capacity: 9,000 gallons • 750 lbs.	for most cubers • 1,500 lbs. for most flakers	
i4000²	9612-37 (4621-11)	NSF

Capacity: 12,000 gallons • 1,000 lbs. for most cubers • 2,000 lbs. for most flakers



MC² and XC² Cartridges

Reduces chlorine taste, odor and other offensive contaminants that can adversely affect the taste of fountain beverages. Pre-coat submicron filtration reduces particles as small as 1/2 micron, and it helps retain carbonation in drinks. NSF registered under NSF/ANSI Standards 42 and 53.

- Pre-coat filtration with Micro-Pure® II antibacterial protection
- Reduces objectionable tastes and odors
- Cyst reduction
- Sanitary quick-change cartridge replacement

MC ²	9612-55 (4621-20)	(NSF)
Capacity: 9,000 gallons		
XC ²	9613-97 (4621-21)	(NSF)

Capacity: 12,000 gallons



BH² and OCS² Cartridges

- Delivers premium quality water for ice and coffee applications
- Designed for applications where the i2000² is too long
- Pre-coat submicron particulate reduction
- Inhibits scale formation
- Taste and odor reduction
- NSF registered under NSF/ANSI standards 42 and 53.

BH ²	9612-51 (4621-12)	(NSF)
Capacity: 3,000 gallons or 6,00	00 pots of coffee • 0.5 gpm max. flow	
OCS ²	9618-07	NCE

Capacity: 1,500 gallons or 3,000 pots of coffee • 0.5 gpm max. flow



OW200L and OW4Plus Cartridges

- Ideal for office or residential water systems
- Unique filter blend uses activated carbon to reduce chlorine taste, odor, and other offensive contaminants
- Reduces lead to below the Federal Action Level of 10 ppb
- Pre-coat submicron technology reduces dirt and particles as small as 1/2 micron
- Inhibits scale build-up in water-using appliances
- NSF registered under NSF/ANSI standards 42 and 53

(NSF)

Capacity: 2,000 gallons

*Everpure® is a trademark of Everpure, Inc., Westmont, IL.

EVERPURE® WATER FILTRATION

EVERPURE® WATER

FILTRATION



4CB5, 7CB5, 4CB5-S, and nu-7CB5-S Cartridges

Carbon Block filter finely polishes water for high-quality beverages and food applications. NSF registered under NSF Standard 42.

- Problem-solving cartridge for high particulate or low flow water pressure areas
- · Taste and odor, chlorine reduction
- Particulate reduction down to 5 microns
- 4CB5-S, and nu-7CB5-S cartridges control scale

4CB5	9617-16 (4621-32)	(NSF)
Capacity: 6,000 gallons		
7CB5	9618-16	(NSF)
Capacity: 10,000 gallons		
4CB5-S	9617-26 (4621-31)	(NSF)
Capacity: 6,000 gallons		
7CB5-S	9618-26 (4621-30)	(NSF)
Canacity 10 000 gallons		

Capacity: 10,000 gallons

4FC5, 7FC5, 4FC5-S, and 7FC5-S Cartridges

New Fiberdyne™ II media with Agion® antimicrobial protection to inhibit potential bacterial growth. Balanced cartridge for optimum performance in varying water qualities. Helps retain the drink's carbonation.

- Increased capacity 25,000 gallons
- Taste and odor reduction
- Particulate reduction

- 2.5 gpm flow rate
- 5 micron rating
- Scale inhibition (4FC5-S and 7FC5-S)

NSF standards 42 and 53		
4FC5	9693-21	NSF)
Capacity: 15,000 gallons		
7FC5	9693-61	NSF.
Capacity: 25,000 gallons		
4FC5-S	9693-31	NSF
Capacity: 15,000 gallons		
7FC5-S	9693-71	NSF.

Capacity: 25,000 gallons

4FC, 7FC, 4FC-S, and 7FC-S Cartridges

New Fiberdyne™ II media with Agion® antimicrobial protection to inhibit potential bacterial growth. $Balanced\ cartridge\ for\ optimum\ performance\ in\ varying\ water\ qualities.\ Improves\ the\ taste\ of\ fountain$ drinks and helps retain the drink's carbonation.

- Taste and odor reduction
- Particulate reduction
- 2.5 gpm flow rate

- 1/2 micron rating
- NSF standards 42 and 53
- Scale inhibition (4FC-S, and 7FC-S only)

4FC	9692-21	(NSF)
Capacity: 15,000 gallons		
7FC	9692-61	NSF
Capacity: 25,000 gallons		
4FC-S	9692-31	NSF
Capacity: 15,000 gallons		
7FC-S	9692-71	NSF

Capacity: 25,000 gallons

Warewashing

Kleenware HTS-11 Scale Control System

Scale control for hot temperature applications such as warewashing and booster heaters. Inhibits limescale buildup and reduces corrosion. Features metering flow through head, high temperature housing and transparent HT-10 cartridge. Maximum feeder inlet temperature: 170.0°F/76.7°C

Kleenware HTS-11	9799-11
HT-10 Replacement cartridge	9799-22

Replacement Cartridges for CUNO®

EFS

The EFS cartridges are replacements that are compatible with the CUNO Series CFS 8000 filter cartridges. Both incorporate a carbon block filter that reduces objectionable tastes and odors, as well as chlorine and other contaminates, providing high-quality beverages and ice. They also reduce extra fine dirt as small as 5 microns. Additionally, the EFS 8002-S provides for the reduction of scale formation.

EFS 8002	9781-10 (4622-20)

Capacity: 10,000 gallons (37,850 liters) • 1.5 gpm flow Replaces CFS-8112, CFS-8720 & CFS-8812

EFS 8002-S 9781-12 (4622-10)

Capacity: 10,000 gallons (37,850 liters) • 1.5 gpm flow Replaces CFS-8112S,CFS-8720S & CFS-8812S

*Everpure® is a trademark of Everpure, Inc., Westmont, IL. *CUNO® is a trademark of 3M. This product is not manufactured, sponsored, or affiliated with 3M.

Other Filtration Products

10" and 20" Coarse Prefilters

A 10" and 20" black housing, each including a 10" and 20" replaceable prefilter cartridge. Filters out larger dirt and rust particles, thereby extending the life of submicron and carbon block filters.

E-10	9795-80 (4621-42)
E-20	9795-90 (4621-44)

Optional: Prefilter bracket kit for all multiple filter head systems manufactured after 2003: 3114-34 (4621-45)



EC110 and EC210

A 10" and 20" 10-micron nominal filtration cartridge for filtering out larger dirt and rust particles, extending the life of primary filters. For use in the E-10 and E-20 housings as well as other 10" and 20" housings.

EC110 (10")	9534-40 (4621-41)
EC210 (20")	9534-20 (4621-43)

SRX Scale Inhibitor Feeder



A complete system for the control of scale in ice, coffee, steam, and combination applications. It dispenses a controlled amount of HydroBlend™ compound, which provides for a more consistent feed and longer life. The system includes a black housing and one cartridge

1 each	9798-45 (4621-05)
O-ti	. l.:4 f ll l4: l - f:l4 l

Optional: Post-filter bracket kit for all multiple filter head systems manufactured after 2003: 3114-35 (4621-06)



IMF-7 and IMF-10

Ice Machine Feeder scale inhibition cartridge. The translucent cartridge allows for easy visual monitoring of the product's usage. The larger IMF-10 will last longer or treat higher volumes of water.

IMF-7	Replacement for AR-X 7" Housing	9799-32 (4621-13)
IMF-10	Replacement for SS-10 Scale Sticks	9799-02 (4621-14)

4JT Flushing/Sanitizing Cartridge



The preferred way to introduce ScaleKleen Scale Remover or other sanitizing agents, such as bleach, into all water-using equipment and vending machines. Fits into existing Everpure heads. Eliminates the need for difficult component disassembly. Easy and convenient to help you clean and maintain equipment.



ScaleKleen™ Scale Remover

Restores equipment to peak operating efficiency by removing scale build-up. Quickly removes limescale from coffee brewers. Ideal for deliming steam and ware washing equipment. Great for office coffee system (OCS) applications. Non-toxic, safe to skin, and won't burn clothing. Sewer system disposable; can be poured down the drain. Use with 4JT Flushing/ Sanitizing Cartridge.

7 oz. packets (24 per case)	9798-33 (4621-17)
2.2 lb. canister (4 per case)	9798-35







CFS Filtration System

A family of replacement cartridges and manifolds designed to service existing CUNO® CFS installations.

A cost-effective water filtration system for food service applications: ice machines, fountain beverages, steam ovens, and drinking water. These systems offer manifold and sanitary quick-change cartridges to fit the existing CUNO CFS brand installations and can also support new filtration installations. CFS is the reliable choice for water filtration to prevent unwanted troubles caused by sediment, scale, or taste and odor existing in CUNO installations.

Sediment – 5 micron	4623-10
Sediment – 5 micron / phosphate	4623-11
Carbon Block5 micron	4623-12
Carbon Block5 micron / phosphate	4623-13

Single Head	4623-01
Twin Head	4623-02
Triple Head	4623-03
Twin Series	4623-06



The CGSYS-22C5S

A matching product for the Tri-Liminator Filtration System, with application and specifications that are nearly identical. For example, the primary cartridge (CG5-20S) will replace both the K00070 and K00174 cartridges, and it has more scale control ability than either of the Tri-Liminator cartridges.

CGSYS-22C5S	9101-24 (4610-30)
Prefilter - EC210	9534-20 (4621-43)
Primary cartridge - CG5-20S	9108-27

Water Filtration



Micro-Plus® & Micro-Carbon 4

The complete all-in-one treatment for ice machines, coffee urns and brewers, humidifiers, steamers, etc. The Micro-Plus "in-line" filters contain 6R Micromet® to control scale, high-grade activated carbon for eliminating objectionable tastes and odors, and filter discs to remove silt and sediment down to 20 microns. Available in four sizes with 1/4" FPT connections. When properly sized, each filter will last up to six months. The Micro-Carbon 4 is available for removing objectionable tastes and odors.

Micro-Plus 2	4615-W3
Micro-Plus 4	4612-W3
Micro-Plus 8	4613-Y8
Micro-Plus 16	4614-Y8
Micro-Carbon 4	4617-24

Application	Micro-Plus 2	Micro-Plus 4	Micro-Plus 8	Micro-Plus 16	Micro-Carbon 4
Water (per day)	12.5 gallons	25 gallons	50 gallons	100 gallons	50 gallons
Ice (per day)	Up to 125 lbs.	Up to 250 lbs.	Up to 500 lbs.	Up to 1000 lbs.	
Coffee (per week)	25 lbs.(1,250 cups)	50 lbs. (2,500 cups)	100 lbs. (5,000 cups)	200 lbs. (10,000 cups)	

Water Filtration - NP Series



NP Series Housings

These housings are designed to hold one of the NP Cartridges used to filter water for ice machines, coffee urns, and other beverage equipment. The NP24DD and NP48DD housings fit specific NP24 or NP48 cartridges for controlling scale, sediment, or objectionable tastes and odors. The NP24DD is equipped with 3/8″ FPT connections and handles up to 4.0 gpm. The NP48DD is equipped with 1/2″ FPT connections and can handle flow rates up to 5.0 gpm.

NP24DD	4704-24
NP48DD	4714-24



6R Micromet®/Carbon Cartridge

A custom cartridge, combining 6R Micromet for scale-control and a carbon block for sediment (10 microns), taste and odor control.

NP24PC	4706-87
NP48PC	4716-87



Carbon Block Cartridge

The NP24C Cartridge fits the NP24DD Housing while the NP48C fits the NP48DD. These carbon blocks will remove most objectionable tastes and odors and are rated to remove particulate down to 10 microns.

NP24C	4701-87
NP48C	4711-87



Sediment Cartridge

The NP24S (5") and the NP48S (10") are made from FDA-approved polypropylene construction and filter down to 5 microns. In addition, the 10" and 20" versions are available in bulk packaging.

NP24S	4702-87
NP48S	4712-87
EC210, 20" (10 microns)	9534-20 (4621-43)



6R Micromet® Cartridge

The NP246R Micromet Cartridge contains 1 pound of 6R Micromet, and it fits the NP24DD Housing. The NP486R Cartridge contains 2 pounds of 6R and fits the NP48DD Housing, with 10 micron filtration.

NP246R	4705-87
NP486R	4715-87



6R Micromet®/Sediment Cartridge

Another custom cartridge within the NP Series, consisting of polypropylene for filtration (5 microns) and phosphate for scale-control.

NP48PS	4717-87
CG5-205, 20"	9108-27



NP Series Brackets

Some installations may require two or three NP Series housings to meet more than one specific water-related condition. This custom installation can be accomplished through the use of one of the NP Series multi-housing brackets.

Two housing brackets	NP2BR
Three housing brackets	NP3BR

	Problem to Solve				Daily Capacities	
Cartridge Type	Sediment	Taste & Odor	Scale	"24's"	"48's"	
"S" Cartridges	х			1800 lbs. (200 gal.)	3600 lbs. (400 gal.)	
"C" Cartridges	х	х		1800 lbs. (200 gal.)	3600 lbs. (400 gal.)	
"6R" Cartridges	х		х	900 lbs. (100 gal.)	1800 lbs. (200 gal.)	
"PC" Cartridges	х	х	х	600 lbs. (65 gal.)	1200 lbs. (135 gal.)	
"PS" Cartridges	х		х	N/A	550 lbs. (60 gal.)	

38

WATER FILTRATION

NATE training now online. Visit us at www.nucalgon.com.

Coil Cleaning: The Clean Coil Program is a comprehensive seminar dedicated to the safe and proper procedures to clean evaporator and condenser coils. The program will help determine which cleaning method should be utilized for a particular job based on the type and condition of the unit. NATE Recognition Classes: 1 hour Continuing Education Accreditation



Indoor Air Quality Management: The seminar covers the past, present and future of indoor air quality (IAQ). Topics covered in the session: how poor IAQ impacts a business, common causes of poor IAQ, and how to prevent poor IAQ from occurring.



NATE Recognition Classes: 1 hour Continuing Education Accreditation

Refrigeration Oils: An in-depth look at industry refrigeration oils (Mineral, Alkylbenzene, nd POE) and when and where to use them. NATE Recognition Classes: 1.5 hours Continuing Education Accreditation



Total System Protection: A thorough look at why burnouts occur, how to prevent them and the proper way to flush a system once a burnout occurs. The training will include acid testing and acid neutralization. NATE Recognition Classes: 1 hour Continuing Education Accreditation



Water Treatment: This seminar will cover the fundamentals of water treatment for cooling towers, evaporative condensers, boilers, and chillers. NATE Recognition Classes: 1.5 hours Continuing Education Accreditation



Ice Machine Treatment and Filtration: A complete guide to "Extending the Life of an Ice Machine." The seminar will answer the questions: why use a filter, what filter should be used, and how to keep the system clean, clear, and running properly. It also addresses all of the water-related problems associated with ice machines. (1.5 hours)

Winter Water Treatment: This program focuses on what a system needs prior to the winter season, including a review of ethylene and propylene glycol, the proper treatments for hot/cold closed systems, and low make-up steam systems. (1 hour)

Energy Savings with A/C Re-New: Learn about a revolutionary product for revitalizing and energizing A/C systems. The seminar will explain how A/C Re-New will help reduce energy costs, improve cooling performance and reduce the system noise. (1 hour)

Food Service Products for Ice & Beverage Filtration: A comprehensive look at the problems associated with ice and beverage filtration as well as treatment options to solve these problems. This seminar covers products for ice makers, coffee brewers, fountain beverage machines, steam ovens, drinking water, and more. (1 hour)

Nu-Calgon Product Line Review: The seminar provides an overview of all the major products that Nu-Calgon offers. The presentation explores when and where to use certain products, as well as explains how using certain products can save time and money. (2 hours)

iWave Air Purifiers: This seminar focuses on Nu-Calgon's iWave line of bio-polar ionization air purifiers. Topics covered in this session: the specific applications and sizing guidelines for each model, how iWave purifies the air by killing mold, bacteria and viruses, and how iWave reduces allergens, smoke, odors and VOCs.

Serving the United States & Canada with the Finest Direct Factory Sales Force in the HVACR Industry 2 7 12 14 6 9

- 1. Seattle, WA
- 2. Northern CA
- 3. Los Angeles, CA
- 4. Orange County, CA
- 5. San Diego, CA
- 6. Phoenix, AZ
- 7. Denver, CO
- 8. San Antonio, TX
- 9. Dallas Fort Worth
- 10. Houston, TX
- 11. St. Paul Minneapolis

- 12. Kansas City, MO
- 13. Baton Rouge, LA
- 14. St. Louis, MO
- 15. Milwaukee, WI
- 16. Chicago, IL
- 17. Indianapolis, IN
- 18. Detroit, MI
- 19. Birmingham, AL
- 20. Columbus, OH
- 21. Atlanta, GA
- 22. Ocala, FL

- 23. Tampa, FL
- 24. Miami, FL
- 25. Raleigh, NC
- 26. Richmond, VA
- 27. Philadelphia, PA
- 28. Syracuse, NY
- 29. Baltimore, MD
- 30. NYC/New Jersey
- 31. Boston, MA
- St. Louis, MO (Hdq.)



Nu-Calgon

2611 Schuetz Rd., St. Louis, MO 63043 Phone: 800-554-5499

WWW.NUCALGON.COM

VOL. 19, NO. 1















