SATCO NUVO

Project Name

Prepared By



IMAGE NOT AVAILABLE

SATCO S29925

40T8/LED/96-850/BP/R17D

Notes

| General | |
|-------------------------|--|
| Status | Active |
| Watts | 40W |
| Volts | 120V-277V |
| Ballast Type | Туре В |
| Shape | Т8 |
| Base | Recessed Double Contact HO/VHO |
| ANSI Base | R17d |
| Nominal Length | 96.00 |
| Finish | White |
| CCT (Kelvin) | 5000 |
| Temperature | Natural Light |
| CRI | 82 |
| Lumens | 5500L |
| Beam Spread | 210 |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Lamp Type | Linear |
| Technology | LED |
| Electrical | |
| Ballasting Requirements | Ballast Bypass |
| Operating Frequency | 50/60 Hz |
| Physical | |
| MOL | 94.00 |
| MOD | 1.00 |
| Additional Information | |
| Additional Info | Suitable for Emergency Lighting only with Satco EM Driver #S8002 |
| Shatter-Proof Type | PET Coated |
| Warranty | 5 Year Limited - T8 LED Bulbs |

| Compliance | |
|-------------------|-------------------------------|
| Safety Listing | cULus |
| Location Rating | Damp |
| Energy Star | No |
| California Status | Lawful for sale in California |
| FCC Compliant | Yes |
| NSF Approved | Yes |





