



Submittal Data, Part # 1101

Closed-Loop Geothermal Installation Hose Kit for 1 Inch FPT Connections



Project Name:	Representative:	
Contractor:	Engineer:	
Ref/P.O.#:	Date:	
Submitted by:	Date:	
Qty:	Part #:	Description

Technical Data

Elbows (2):	1" MPT (National Pipe Tapered, Male) x 1" Hose Barb with 1/4" FPT (National Pipe Tapered, Female) Port, Brass
Straight Fittings (2):	1" MPT X 1" Hose Barb, Brass
Pressure/ Temperature Fittings (2):	1/4" MPT, Brass with EPDM Core
Hose Clamps (8):	Size 20, 3/4" to 1-3/4", All stainless steel, Torque specification 35 in-lbs
Hose (12 ft) [305 mm]:	1" Nominal Internal Diameter, EPDM Synthetic Rubber Tube and Cover, RMA Class C

Temperature

Max. Fluid Temperature: 140°F [60°C]
 Min. Fluid Temperature: 20°F [-7°C]
 Max. Operating Pressure: 150 psi [10.3 Bar]

Approved Antifreeze

Ethanol
 Methanol
 Propylene Glycol



GEO-FLO PRODUCTS CORPORATION
 905 Williams Park Drive
 Bedford, IN 47421
 Phone: 812-275-8513 Fax: 812-275-8523
 www.geo-flo.com