Product data sheet Characteristics

ZB4BC4

red Ø40 mushroom pushbutton head Ø22 spring return

Product availability: Stock - Normally stocked in distribution facility

Price* : 29.40 USD



Main

| Main | | <u> </u> |
|-------------------------------|--------------------------------------|--------------------------------|
| Range of product | Harmony XB4 | |
| Product or component type | Head for non-illuminated push-button | |
| Device short name | ZB4 | |
| Bezel material | Chromium plated metal | : <u>:</u> : <u>:</u> .g |
| Mounting diameter | 0.87 in (22 mm) | |
| Sale per indivisible quantity | 1 | |
| Shape of signaling unit head | Round | |
| Type of operator | Spring return | |
| Operator profile | Red mushroom Ø 40 mm unmarked | |
| | | 7 |

Complementary

| CAD overall width | 1.57 in (40 mm) | |
|-----------------------------|---|--|
| CAD overall height | 1.57 in (40 mm) | |
| CAD overall depth | 2.05 in (52 mm) | |
| Mechanical durability | 5000000 cycles | |
| Electrical composition code | C1 <= 9 contacts using single blocks in front mounting C2 <= 9 contacts using single and double blocks in front mounting C11 <= 3 contacts using single blocks in front mounting C15 1 contacts using single blocks in front mounting | |

Environment

| | | _ |
|---------------------------------------|--------------------------------------|-----------|
| Protective treatment | TH | tation |
| Ambient air temperature for storage | -40158 °F (-4070 °C) | |
| Ambient air temperature for operation | -40158 °F (-4070 °C) | |
| Overvoltage category | Class I conforming to IEC 60536 | i. F |
| IP degree of protection | IP69 IP66 conforming to IEC 60529 | isclaimer |

| | IP69K | | |
|---------------------------|---|--|--|
| NEMA degree of protection | NEMA 13 NEMA 4X | | |
| IK degree of protection | IK06 conforming to IEC 50102 | | |
| Standards | EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 JIS C 4520 UL 508 CSA C22.2 No 14 | | |
| Product certifications | BV CSA DNV GL LROS (Lloyds register of shipping) RINA UL listed | | |
| Vibration resistance | 5 gn (f = 2500 Hz) conforming to IEC 60068-2-6 | | |
| Shock resistance | 30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27 | | |

Ordering and shipping details

| <u> </u> | | | |
|-----------------------|-------------------------------------|--|--|
| Category | 22468 - PUSHBUTTONS,22MM(METAL) NEW | | |
| Discount Schedule | CS2 | | |
| GTIN | 00785901354284 | | |
| Nbr. of units in pkg. | 1 | | |
| Package weight(Lbs) | 0.170000000000001 | | |
| Returnability | Υ | | |
| Country of origin | CZ | | |
| | | | |

Contractual warranty

| Warranty period | 18 months | |
|-----------------|-----------|--|