

Rigid Conduit Bodies with Cover and Gasket

Threaded T Type

Features

- Threaded T type with cover and gasket
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die cast
- Cover - Stamped steel
- Gasket - Neoprene rubber

Standard Finish

- Powder coat


Applicable Third Party Standards

- UL Standard: UL 514A - UL 514D
- Fed. Spec: W-C-586D, A-A-50563
- NEMA: FB 1-2014 - NEMA 3R



E195124

UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1



Catalog Number	UPC	Size	Wire Size		Unit Carton	Ship Case	Weight/Case	Inches		
			Max. Number	Max. Size				A	B	C
T1CG	21731	1/2"	1	6 AWG	10	100	38	4.72	1.37	1.33
T2CG	21741	3/4"	2	6 AWG	10	50	30	5.57	1.625	1.54
T3CG	21751	1"	3	6 AWG	5	25	20	6.46	1.90	1.74
T4CG	21761	1-1/4"	3	2 AWG	2	10	19	8.528	2.77	2.49
T5CG	21771	1-1/2"	3	2 AWG	2	10	21	8.528	2.77	2.49
T6CG	21781	2"	3	2/0 AWG	---	5	10	10.831	3.335	3.10
T7CG	21791	2-1/2"	3	4/0 AWG	---	1	4	13.50	4.06	5.825
T8CG	21801	3"	3	250 MCM	---	1	5	13.50	4.685	5.825
T9CG	21811	3-1/2"	3	350 MCM	---	1	12	15.937	5.45	7.06
T10CG	21821	4"	4	350 MCM	---	1	9	15.937	5.45	7.06