



UV Lamp Identification*


*Part numbers are etched on glass

RESIDENTIAL


TUVL-MINI




TUVL-111




TUVL-111P




TUVL-211




TUVL-211P




TUVL-115




TUVL-115P




TUVL-115P-OS



TUVL-200EZ




TUVL-215




TUVL-215P



TUVL-215P-OS




TUVL-200EZ-OS




COMMERCIAL


TUVL-ICE




TUVCL-132, TUVCL-132HO




TUVCL-132HO-TF, TUVCL-232-TF




TUVCL-146



TUVCL-246-TF



TUVCL-160, TUVCL-160HO



TUVCL-160HO-TF, TUVCL-260-TF





UV Lamp Specifications

Part Number	Warranty	Length	Electrical	UV-C Watts	Output μW/cm2 @ 1 Meter	Fresh-Aire UV Product
RESIDENTIAL						
TUVL-MINI	1 Year	9"	5 mA, 4W	1.0	10	Mini UV
TUVL-111	1 Year	9.75"	425 mA, 17W	5.7	57	APCO RT
TUVL-111P	1 Year	9.75"	425 mA, 17 W	5.7	57	APCO Mag11
TUVL-211	2 Year	9.75"	425 mA, 17 W	5.7	57	APCO RT
TUVL-211P	2 Year	9.75"	425 mA, 17 W	5.7	57	APCO Mag11
TUVL-115	1 Year	14.5"	425 mA, 17 W	5.7	57	APCO
TUVL-115P	1 Year	14.5"	425 mA, 17 W	5.7	57	AHU Series 1, Blue-Tube, APCO Mag15
TUVL-115P-OS	1 Year	14.5"	425 mA, 17 W	5.7	57	AHU Series 1, Blue-Tube
TUVL-215	2 Year	14.5"	425 mA, 17 W	5.7	57	APCO
TUVL-215P	2 Year	14.5"	425 mA, 17 W	5.7	57	AHU Series 1, Blue-Tube, APCO Mag15
TUVL-215P-OS	2 Year	14.5"	425 mA, 17 W	5.7	57	AHU Series 1, Blue-Tube
TUVL-200F-OS	2 Year	14.25"	425 mA, 17 W	5.7	57	Purity
COMMERCIAL						
TUVL-ICE	2 Year	6.75"	400 mA, 10 W	1.5	15	ICE UV
TUVL-200EZ	1 Year	14.25"	425 mA, 17 W	5.7	57	Tight-Fit Kit
TUVL-200EZ-OS	1 Year	14.25"	425 mA, 17 W	5.7	57	Tight-Fit Kit
TUVCL-132	1 Year	32"	400 mA, 44 W	17	165	Commercial Series 32"
TUVCL-132HO	12000 Hr	32"	800 mA, 80 W	33	300	Commercial Series 32" High Output
TUVCL-132HO-TF	12000 Hr	32"	800 mA, 80 W	33	300	Commercial Series 32" High Output
TUVCL-232-TF	2 Year	32"	400 mA, 44 W	17	165	Commercial Series 32"
TUVCL-146	1 Year	46"	400 mA, 54 W	19	190	Commercial Series 46"
TUVCL-246-TF	2 Year	46"	400 mA, 54 W	19	190	Commercial Series 46"
TUVCL-160	1 Year	60"	400 mA, 68 W	28	250	Commercial Series 60"
TUVCL-260-TF	2 Year	60"	400 mA, 68 W	28	250	Commercial Series 60"
TUVCL-160HO	12000 Hr	60"	800 mA, 130 W	52	400	Commercial Series 60" High Output
TUVCL-160HO-TF	12000 Hr	60"	800 mA, 130 W	52	400	Commercial Series 60" High Output

Lamp Type

2 Year lamps feature a shielded quartz hot filament. All others (except TUVL-MINI) have an unshielded quartz hot filament

Operating Temperature

Fresh-Aire UV lamps are designed to operate between 35° to 185° F, 100% humidity.

UV Spectrum

All lamps are 100% 254nm UV-C, except those designated -OS, which are 90% 254nm - 10% 185nm UV-C

Teflon® Coating

Lamps designated with -TF feature a protective Teflon® coating.



800-741-1195

WWW.FRESHAIREUV.COM

Made in USA

