

## End Cap with Vent, R32

Submittal Information  
Revision B: Dec. 15, 2010

### Project Information

Job Name:	
Location:	Part No. Ordered:
Engineer:	Date Submitted:
Contractor:	Submitted By:
Manufacturer's Representative:	Approved By:

### Technical Data

Material:	UNS C3850 Brass
Maximum Working Pressure:	145 psi
Maximum Temperature/Flow:	220°F (104°C)/21.0 gpm
Connection:	1¼" BSP



### Product Information and Application Use

The End Cap with Vent, R32, caps the end of the TruFLOW™ Jr. Modular Manifolds. It comes complete with swivel drain valve and manual air vent. Required gasket (A2403232) is included.

✓ Description	Part Number	Dimensions			Weight
		Length	Width	Height	
The End Cap with Vent, R32	A2803250	2.75"	1.75"	3.500"	0.900 lbs.
Manifold Gasket, spare part	A2403232	O.D.	I.D.	Thickness	0.005 lbs.
		1.55"	1.24"	0.093"	

### Installation

Use with TruFLOW Jr. Manifolds (not preassembled). Use the End Cap for the top manifold, following procedures outlined in the Uponor Radiant Installation Handbook.

### Standards

N/A

### Codes

N/A

### Listings

N/A

### Related Applications

Radiant Heating and Cooling Systems

### Contact Information

Uponor, Inc.  
5925 148<sup>th</sup> Street West  
Apple Valley, MN 55124 USA  
Phone: (800) 321-4739  
Fax: (952) 891-2008  
www.uponor-usa.com

Uponor Ltd.  
2000 Argentia Rd., Plaza 1, Ste. 200  
Mississauga, ON L5N 1W1 CANADA  
Phone: (888) 994-7726  
Fax: (800) 638-9517  
www.uponor.ca