



This item includes:



Item No.: 221-412

COMPACT Splicing Connector; for all conductor types; max. 4 mm²; 2-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent

Item No.: 221-413

COMPACT Splicing Connector; for all conductor types; max. 4 mm²; 3-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent

Item No.: 221-415

COMPACT Splicing Connector; for all conductor types; max. 4 mm²; 5-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent

Item No.: 221-500

Mounting carrier; 221 Series - 4 mm²; for DIN-35 rail mounting/screw mounting; orange

4

Physical data

| | |
|--------|------------------------|
| Width | 260 mm / 10.236 inches |
| Height | 63 mm / 2.48 inches |
| Depth | 155 mm / 6.102 inches |

Material data

| | |
|----------------------|--|
| Note (material data) | Information on material specifications can be found here |
| Fire load | 14.701 MJ |
| Weight | 836.1 g |

Commercial data

| | |
|-----------------------|---------------|
| eCl@ss 10.0 | 27-14-11-04 |
| eCl@ss 9.0 | 27-14-11-04 |
| ETIM 8.0 | EC000446 |
| ETIM 7.0 | EC000446 |
| PU (SPU) | 1 pcs |
| Packaging type | Box |
| Country of origin | DE |
| GTIN | 4055143616997 |
| Customs tariff number | 85369010000 |

Environmental Product Compliance

| | |
|------------------------|-------------------------|
| RoHS Compliance Status | Compliant, No Exemption |
|------------------------|-------------------------|

Downloads

Environmental Product Compliance

| | |
|--|--|
| Compliance Search | |
| Environmental Product Compliance 887-952 | |

Documentation

| | | | |
|----------|------------|------------------|--|
| Bid Text | | | |
| 887-952 | 19.02.2019 | xml 2.76 KB | |
| 887-952 | 23.01.2019 | docx 14.93 KB | |

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com