

radiant Collection radiant® Smart 3-Way Dimmer Gateway Kit With Netatmo, White (2-Pack) Part No. WNRKH532WH



Smart Lighting lets you set the exact lighting you need, from anywhere, adding safety and convenience to your home. And delivering it all with unprecedented range and reliability, radiant® with Netatmo leverages leading Netatmo technology to provide an ideal solution for larger homes with many smart products. Kit includes a Smart Surface-Mount Gateway (WNRH2WH), a Smart Tru-Universal Dimmer (WNRL50WH) and a Wireless Smart Dimmer (WNRL63WH) with Netatmo, plus Screwless Wall Plates. Establish a dedicated network with the Gateway, then install the Smart Tru-Universal Dimmer in place of an existing switch/dimmer for control of lights, from anywhere, through the Legrand Home + Control app. A Tru-Universal Dimmer, it works with virtually any 120V bulb or fixture. To gain easy 3-way dimming control, mount the Wireless Smart Dimmer to any wall or surface – no wiring or cutting required. Add more Smart Switches, Dimmers and Outlets with Netatmo (up to 98 per Gateway) to expand your system.

Features & Benefits

Includes everything you need to install smart, 3-way control

Features ultra-reliable performance through a robust and dedicated mesh-network that actually strengthens with every "with Netatmo" device you add

Smart Tru-Universal Dimmer works with virtually any 120V dimmable bulb or fixture (excludes 0-10V)

Long-lasting and battery-powered, the Wireless Smart Dimmer pairs with a Smart Tru-Universal Dimmer and mounts to any wall or surface for easy 3-way control of lights. Adhesive included

Part of the radiant with Netatmo solution, which flexibly fits a home's unique needs with a variety of supported smart switches, dimmers and outlets (including wireless switches and dimmers)

The foundation of a radiant with Netatmo solution, the surfacemount Gateway is cleverly designed to install easily beside an existing single-gang switch or outlet, no back box or network wiring required

Controls and dims lights via smartphones and tablets using the Legrand Home + Control app. Even schedule lights to turn on/off automatically, create groups, set scenes and monitor energy usage

Smart Tru-Universal Dimmer installs easily in place of an existing switch or dimmer (neutral wire required)

Compatible with other smart products through Amazon Alexa, Google Assistant and Apple HomeKit, as well as with home automation systems

Screwless Wall Plate included. Coordinate with other designer switches and outlets available from the radiant® Collection for a cohesive, sophisticated look

Specifications

General Info

Product Line	Pass & Seymour	Color	White
Finish	Matte	UPC Number	785007442120
Country Of Origin	China	Features	Wireless, Smart Lighting, With Netatmo

Residential/Commercial	Standard	RoHS, FCC, IC, UL, cULus
1-Year Limited Warranty	Туре	Dimmer
d Party Agencies		
E60730-1	cULus Listed	Yes
Yes		
on		
Yes		
n		
Incandescent, Halogen & ELV (FWD): 700W, MLV (FWD): 500VA, LED/CFL/EFL (FWD): 450W / 3.8A, Incandescent, Halogen & ELV (REV): 450W, LED/CFL/EFL (REV): 250W / 2.1A	Compatibility	Amazon Alexa, Google Assistant, Apple HomeKit
120V 450W (CFL), 120V 8A (EFL), 120V 700W (ELV), 120V 5A (Fan Control), 120V 16A (Fluorescent), 120V 700W (Halogen), 120V 700W (Incandescent), 120V 450W (LED), 120V 1600VA (MLV)	Lighting Types	Incandescent/Halogen/LED
Tru-Universal	Environmental Conditions	95 (relative humidity, non- condensing) pct
)	1-Year Limited Warranty d Party Agencies E60730-1 Yes In Section 1 Incandescent, Halogen & ELV (FWD): 700W, MLV (FWD): 500VA, LED/CFL/EFL (FWD): 450W / 3.8A, Incandescent, Halogen & ELV (REV): 450W, LED/CFL/EFL (REV): 250W / 2.1A 120V 450W (CFL), 120V 8A (EFL), 120V 700W (ELV), 120V 5A (Fan Control), 120V 16A (Fluorescent), 120V 700W (Halogen), 120V 700W (Incandescent), 120V 450W (LED), 120V 1600VA (MLV)	1-Year Limited Warranty d Party Agencies E60730-1 Yes Incandescent, Halogen & ELV (FWD): 700W, MLV (FWD): 500VA, LED/CFL/EFL (FWD): 450W / 3.8A, Incandescent, Halogen & ELV (REV): 450W, LED/CFL/EFL (REV): 250W / 2.1A 120V 450W (CFL), 120V 8A (EFL), 120V 700W (ELV), 120V 5A (Fan Control), 120V 16A (Fluorescent), 120V 700W (Halogen), 120V 700W (Incandescent, 120V 450W (LED), 120V 1600VA (MLV)