



Packaged Terminal Air Conditioners

Uncompromising reliability from the brand you trust

Hotpoint[®]

A man with a beard, wearing a dark suit and a white shirt, is lying in a bed with white linens and a green pillow. He is holding a smartphone in his hands and looking at the screen. The background shows a window with grey curtains.

Hotpoint®

A History of Dependability

Founded in 1903, Hotpoint prides itself in creating products that make comfort affordable. Whether it's with a revolutionary redesign of the iron or the first electric range cooktop, we have always honored our customers' need for products that make everyday life easier, all at a price they could afford.

Today, Hotpoint continues that legacy with Packaged Terminal Air Conditioners that lead the way in durability, affordability and ease of use and installation. Because your guests' comfort and your success matter to us.

Hotpoint® Packaged Terminal Air Conditioners

Air Conditioner with Electric Heat

MODEL	AH11E07D3B	AH11E09D3B	AH11E12D3B	AH11E15D3B
BTU	7,000	9,000	12,000	15,000
EER	11.9	11.3	10.7	9.7
VOLTS	230/208	230/208	230/208	230/208

Air Conditioner/Heat Pump with Backup Electric Heat

MODEL	AH11H07D3B	AH11H09D3B	AH11H12D3B	AH11H15D3B
BTU	7,000	9,000	12,000	15,000
EER	11.9	11.4	10.5	9.7
COP	3.4	3.4	3.2	3.0
VOLTS	230/208	230/208	230/208	230/208



Performance & Reliability Features

Backed by an Industry Leader

3-Speed Fan

Give guests control over their comfort with three fan speeds to choose from.

4-Temperature Limiting Options

Easily select one of four temperature ranges for peak efficiency and total customer comfort.

Intuitive Display

Allow guests to easily customize their preferred settings and reduce maintenance calls with an easy-to-use control panel.

Power Cord (LCDI) Included

Hotpoint PTACs come with everything needed for a quick and easy installation.

Automatic Emergency Heat

Keep guests comfortable with a heating option that uses electric resistance heat in heat-pump mode.

Freeze and Frost Protection

Automatic freeze and indoor frost control keep units operating in peak condition.

Auto Power Recovery

In case of power failures, units automatically resume their operation when power restores, reducing maintenance calls.

Self-Diagnostics

Quickly and easily identify service needs with a nine-point diagnostic code system.

1 -Year Full Parts and Labor Warranty

5 -Year Limited Warranty

Additional Features

Remote thermostat compatibility

Works with central desk control systems

Energy-efficient heat pump models available

Tangential fan for smooth air flow and sound

Heat pump models include staged heating

Removable filters for easy maintenance

With a long history of creating durable products at an affordable price, Hotpoint is your trusted PTAC brand.



Chassis	Wall Case (Sold Separately)
Front Panel	Grille (Sold Separately)

Built to Withstand the Elements

No matter how it feels outside, Hotpoint PTACs are engineered with durable materials to provide unwavering comfort inside.

See more at [Hotpoint.com](https://www.hotpoint.com)

Hotpoint PTAC Nomenclature

A	H	1	1	H	0	9	D	3	B
Brand H=Hotpoint® PTAC	Unit Series Chassis series			Nominal Cooling Capacity 07=7,000 BTUH cooling 09=9,000 BTUH cooling 12=12,000 BTUH cooling 15=15,000 BTUH cooling			Heater Watts/Amps 2=2.4 kW; 15 amp 3=3.4 kW; 20 amp 5=5.0 kW; 30 amp		
	Unit Type E=cooling with electric resistance heat H=cooling/heat pump with backup electric heat			Voltage/Phase/Frequency D=230/208 volt, single phase, 60 Hz E=265 volt, single phase, 60 Hz			Special Features B=base unit		

Product Specifications

Hotpoint Heat/Cool Series	Air Conditioner with Electric Heat				Air Conditioner/Heat Pump with Backup Electric Heat			
	AH11E07D3B	AH11E09D3B	AH11E12D3B	AH11E15D3B	AH11H07D3B	AH11H09D3B	AH11H12D3B	AH11H15D3B
Voltage	230/208	230/208	230/208	230/208	230/208	230/208	230/208	230/208
Cooling Capacity								
Cooling BTUH	7300/7100	9200/9000	12000/11800	14700/14500	7200/6800	9000/8800	12000/11800	14700/14500
EER (BTU/Watt)	11.9	11.3	10.7	9.7	11.9	11.4	10.5	9.7
COP					3.4	3.4	3.2	3.0
Features								
Refrigerant Type	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A
Electronic Controls	●	●	●	●	●	●	●	●
LCDI Power Cord	●	●	●	●	●	●	●	●
Remote Thermostat Capable	●	●	●	●	●	●	●	●
Slide-In Chassis	●	●	●	●	●	●	●	●
Discharge Grille	1-position	1-position	1-position	1-position	1-position	1-position	1-position	1-position
Fan Motor	2	2	2	2	2	2	2	2
Fan Speeds	3	3	3	3	3	3	3	3
Heat - Cool	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Rotary Compressor	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Fan Cycle Control	●	●	●	●	●	●	●	●
Freeze Control	●	●	●	●	●	●	●	●
Automatic Indoor Frost Control	●	●	●	●	●	●	●	●
Heat pump with Resistance Heat Backup					●	●	●	●
Automatic Emergency Heat					●	●	●	●
Auto Power Recovery	●	●	●	●	●	●	●	●
Central Desk Control Capable	●	●	●	●	●	●	●	●
Fresh Air Vent	Concealed Manual Vent Control Vent Air Filter	Concealed Manual Vent Control Vent Air Filter	Concealed Manual Vent Control Vent Air Filter	Concealed Manual Vent Control Vent Air Filter	Concealed Manual Vent Control Vent Air Filter	Concealed Manual Vent Control Vent Air Filter	Concealed Manual Vent Control Vent Air Filter	Concealed Manual Vent Control Vent Air Filter
Outdoor Vent / Exhaust	●	●	●	●	●	●	●	●
Weight & Dimensions								
Overall Dimensions (including room cover) (WxHxD)	42 x 16 x 21				42 x 16 x 21			
Net Weight	99 lb	105 lb	112 lb	113 lb	101 lb	107 lb	116 lb	116 lb
Approximate Shipping Weight	124 lb	130 lb	136 lb	137 lb	127 lb	132 lb	140 lb	141 lb

Accessories to add

Model #	Description
RAB80	Hotpoint Wall Case
RAG70	Hotpoint Grille
RAA70	Hotpoint Filter



Hotpoint Wall Case
RAB80



Hotpoint Grille
RAG70



Hotpoint Filter
RAA70