

Care and Cleaning Instructions



GLOSS FINISH

Tape residue left from labels can be removed by using paste wax and elbow grease.

Preserve the lustre by occasional cleaning and waxing. Use only liquid, non-abrasive cleaners. Afterwards, apply a light coating of non-yellowing wax and polish. Remove hard water scale and rust stains with mild vinegar and water solution followed by an automotive polishing compound.

Many difficult stains can be avoided by attention to proper use of your molded product. These steps can be taken to remedy unusual cleaning problems.

Grease stains and oil residues can be removed by kerosene, mineral spirits or butylcellosolve available from paint outlets.

Mold and mildew can be removed with a diluted solution of Clorox[®] or Lysol[®]. Never let pure Clorox[®] or Lysol[®] come in contact with finished surface. Hair dye or shoe polish stains can also be removed by using polishing compound.

Minor surface scratches can be buffed out using the polishing compound. Deeper scratches or burns require light sanding with a wet #600 sandpaper. Sand lightly with a circular motion in as confined an area as possible. Wet area amply while sanding. Remove the minor scratches, which result from sanding, by buffing with polishing compound. Applying clear fingernail polish can repair small chips, then follow the instructions for sanding out scratches.

Cigarette stains can be removed by using Bon Ami applied with a toothbrush. After removing the stain, polish out the area with toothpaste.

Certain chemical substances can seriously mar the surface even during brief periods of contact. Protect the surface from contact with these harmful reagents:

- * Clorox[®] and Hypochlorite bleaches
- * Fingernail polish remover
- * Hydrogen Peroxide in any concentration
- * Drano[®] or Lye solutions
- * Sani-flush or other Sodium Bisulfate compounds
- * Paint strippers containing Methylene Chloride, Comet[™],
- * AJAX[™] or other abrasive cleaners



2700 Atlantic Blvd., N.E. Canton, Ohio 44705-3923 Telephone: 330-453-8437 or 800-288-4095

Website: www.amisurfaces.com

Email: amiinfo@amitops.com

Fax: 330-453-4913

4-1-15